


## T800-EX FULLY RUGGED TABLET



- 8.1" HD LumiBond display for better viewing experience
- MIL-STD-810H and IP65 certified
- Enhanced enterprise security with TPM2.0, Windows disk encryption



T800-EX 3D demo



## SPECIFICATIONS

### Generation

G2

### Operating System

Windows 10 IoT Enterprise

### Mobile Computing Platform

Intel® Atom Processor x7-Z8750 1.6GHz,  
burst up to 2.56GHz  
- 2MB Cache

### VGA Controller

Intel® HD Graphics

### Display

8.1" Wide Viewing Angle TFT LCD WXGA (1280 x 800)  
Protection film  
600 nits LumiBond display with  
Getac sunlight readable technology

### Storage & Memory

4GB LPDDR3  
Optional: 8GB LPDDR3

128GB eMMC  
Optional: 256GB eMMC

### Keyboard

Power button  
5 tablet programmable buttons

### Pointing Device

Touchscreen  
- Capacitive multi-touch screen  
- Optional: Dual mode touchscreen  
(multi-touch and digitizer)

### Expansion Slot

Optional: SnapBack add-on: 2<sup>nd</sup>  
expanded battery  
Optional: 1D/2D imager barcode reader x 1

### I/O Interface

FHD webcam x 1  
8M pixels auto focus rear camera x 1  
Audio in/out combo x 1  
DC in Jack x 1  
USB 3.2 Gen 1 Type-A x 1  
Micro HDMI 1.4 x 1  
Optional: SIM card slot x 1 (Mini-SIM, 2FF) <sup>i</sup>

### Communication Interface

Intel® Wi-Fi 6 AX200, 802.11ax  
Bluetooth (v5.2) <sup>ii</sup>  
Optional: Dedicated GPS  
Optional: 4G LTE mobile broadband <sup>i</sup>

### Security Feature

TPM 2.0

### Power

AC adapter (65W, 100-240VAC, 50/60Hz)  
Li-ion battery (7.4V, typical 4200mAh;  
min. 4080mAh)

### Dimension (W x D x H) & Weigh

227 x 151 x 24 mm (8.93" x 5.94" x 0.94") <sup>iii</sup>  
0.91kg (2lbs) <sup>iii</sup>

### Rugged Feature

MIL-STD-810G certified  
IP65 certified  
Vibration & 6ft (1.8m) drop resistant <sup>iv</sup>  
ATEX & IECEx certified

### Environmental Specification

Temperature <sup>v</sup>:  
- Operating: -21°C to 50°C / -6°F to 122°F  
- Storage: -51°C to 71°C / -60°F to 160°F

Humidity:  
- 95% RH, non-condensing

### Explosion Protection

ATEX/IECEx Zone 2/22  
Ex II 3G Ex ic op is IIC T4 Gc  
Ex II 3D Ex ic op is IIIB T130°C Dc

### Pre-installed Software

Getac Utility  
Getac Camera  
Getac Barcode Manager <sup>vi</sup>  
Getac Driving Safety Utility (trial version)  
Getac KeyWedge Barcode Reader Utility  
(trial version)  
Optional: Absolute Persistence®

### Optional software

Getac Driving Safety Utility  
Getac KeyWedge Barcode Reader Utility  
Getac Device Monitoring System (GDMS)  
Getac VGPS Utility <sup>vii</sup>

### Accessories

Battery (7.4V, typical 4200mAh;  
min. 4080mAh)  
AC adapter (65W, 100-240VAC)  
Capacitive stylus with tether

**Optional:**  
Battery (7.4V, typical 4200mAh;  
min. 4080mAh)  
2<sup>nd</sup> expanded battery  
(14.4V, 2100mAh)  
AC adapter (65W, 100-240VAC)  
Digitizer pen  
Capacitive stylus with tether  
Protection film  
Shoulder strap (2-point)

### Bumper-to-Bumper warranty

Les accidents surviennent quand on s'y attend le moins, en particulier avec les produits renforcés soumis à des conditions difficiles, et peuvent alors engendrer une mise hors service des équipements ainsi que des périodes d'interruption très coûteuses. C'est pourquoi Getac propose de prendre en charge les dommages accidentels dans sa garantie Bumper-to-Bumper, afin de réduire les coûts informatiques de votre entreprise. La garantie Bumper-to-Bumper, c'est la tranquillité d'esprit assurée, avec le meilleur service logistique Pack & Collect d'Europe, puis la réparation et le renvoi rapide par les experts internes de Getac. En quelques jours seulement, vous êtes certain de récupérer vos appareils opérationnels.

### Standard

Garantie Bumper-to-Bumper de 3 ans

# T800-EX FULLY RUGGED TABLET

- I. Units with 4G LTE option come with an embedded SIM card slot.
- II. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- III. Weight and dimensions vary from configurations and optional accessories.
- IV. Drop test results vary from configurations and optional accessories.
- V. Tested by an independent third-party test lab following MIL-STD-810H.
- VI. Available when barcode reader option is selected.
- VII. Models require either embedded or standalone GPS module.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

# Getac



GETAC TECHNOLOGY CORPORATION

12, avenue du Québec Bâtiment Goyave 91140  
Villebon sur Yvette Tel: +33 160 12 80 60  
Sales-Getac-France@getac.com |  
www.getac.com/fr/

Copyright © 2023 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Les informations sont fournies ici pour référence seulement, les spécifications disponibles doivent faire l'objet d'un devis sur demande.