


## ZX10-EX FULLY RUGGED TABLET



- ATEX & IECEx Zone 2/22 explosive atmosphere certified
- Qualcomm® QCS6490, Octa-core Processor
- 10.1" LumiBond display with Getac sunlight readable technology (1,000 nits)
- 6ft drop, MIL-STD-810H and IP66 certified
- Multiple configurations with enterprise-level management tools in a light form factor



SPECIFICATIONS

Generation

G2

Operating System

Android™ 13.0

Mobile Computing Platform

Qualcomm® QCS6490, Octa-core 1.9GHz

Max. 2.7GHz

Graphics

Qualcomm® Adreno™ 643 GPU

NPU

Qualcomm® Hexagon™ Processor,  
up to 13 TOPS with 6th Qualcomm AI Engine

Display

10.1" TFT LCD WUXGA (1920 x 1200)  
Anti-static protection film  
1000 nits LumiBond display with Getac sunlight  
readable technology

Storage & Memory

8GB LPDDR5

128GB UFS

Optional: 256GB UFS

Device Button

Power button  
4 tablet programmable buttons

Pointing Device

Touchscreen  
- Dual mode touchscreen (multi-touch and digitizer)

Expansion Slot

Optional: Smart card reader  
Optional: 1D/2D imager barcode reader  
Optional: NFC <sup>i</sup>

I/O Interface

8MP webcam x 1  
16MP auto focus rear camera x 1  
Audio in/out combo x 1  
USB 2.0 (Host) x 1  
USB 3.2 Gen 1 Type-C w/ DP & PD x 1  
MicroSD x 1  
Optional: SIM card slot x 1 (Nano-SIM, 4FF)

Communication Interface

Wi-Fi 6E 802.11ax  
Bluetooth (v5.2) <sup>ii</sup>  
Optional: 4G LTE mobile broadband <sup>iii</sup>  
Optional: 5G Sub-6 <sup>iii</sup>  
Optional: Dual SIM (Nano-SIM 4FF and e-SIM) <sup>iii</sup>  
Optional: Dedicated L1/L5 GPS <sup>iv</sup>

Security Feature

Kensington lock  
Optional: Smart card reader  
Optional: NFC <sup>i</sup>

Power

Li-ion battery (3.88V, typical 4990mAh; min. 4870mAh)  
+ Battery bay cover

Dimension (W x D x H) & Weight

275 x 204 x 20.05mm (10.83 " x 8.03" x 0.79")  
1.05kg (2.31lbs) <sup>v</sup>

Rugged Feature

MIL-STD-810H certified  
IP66 certified  
Vibration & 6 feet (1.8m) drop resistant <sup>vi</sup>  
ATEX & IECEx certified

Environmental Specification

Temperature <sup>vii</sup>:  
- Operating: -21°C to 55°C / -5.8°F to 131°F  
- Storage: -51°C to 71°C / -60°F to 160°F  
Humidity:  
- 95% RH, non-condensing

Explosion Protection

ATEX/IECEx Zone 2/22  
Ex II 3G Ex ic op is IIC T4 Gc  
Ex II 3D Ex ic op is IIIB T130°C Dc

Pre-installed Software

Getac Camera  
Getac Input Method  
Getac Driving Safety Utility (trial version)  
Getac settings and Google applications (Search, Chrome,  
Gmail, Maps, YouTube, Play, Drive, YouTube music,  
Google TV, Meet and photos)  
Getac Log Tool  
Getac Diagnostic  
Getac Monitoring (trial version) agent/SDK  
Getac Management (trial version) agent/SDK

Optional software

Getac Driving Safety Utility  
Getac Monitoring  
Getac Management  
Getac OEMConfig

Accessories

Battery (3.88V, typical 4990mAh; min. 4870mAh)

Optional:

Carry bag  
Battery (3.88V, typical 4990mAh; min. 4870mAh)  
High capacity battery  
(3.88V, typical 9980mAh; min. 9740mAh)  
Multi-Bay charger (Dual-Bay)  
Multi-Bay charger (Eight-Bay)  
65W USB-C AC adapter  
Digitizer pen with tether  
Anti-static protection film  
Hard handle <sup>viii</sup>  
Shoulder strap (2-point)  
Shoulder harness (4-point; handsfree)  
Rotating hand strap with kickstand

Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.  
That is why Getac has introduced accidental damage as standard under our Bumper-toBumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee.  
That means you can depend on us to have your unit back in service within days

Standard

3 years Bumper-to-Bumper

ZX10-EX FULLY RUGGED TABLET

- I. 13.56MHz contactless NFC (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- II. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- III. One physical SIM card slot and one eSIM. Network service may vary depending on local telecommunication providers.
- IV. Support GPS, GLONASS, Galileo and BeiDou. Only available in the US, UK, EU, Australia and New Zealand.
- V. Weight and dimensions vary from configurations and optional accessories; optional high-capacity batteries add approx. 7.65mm (H), 140g.
- VI. Drop test results vary from configurations and optional accessories.
- VII. When using AC power, the device operates in temperatures as low as -29°C (-20°F), as tested by an independent third-party laboratory following MIL-STD-810H standards. For battery-only operation, it functions down to -15°C (5°F) with one standard battery, -21°C (-6°F) with two standard batteries, and -29°C (-20°F) with two high-capacity batteries.
- VIII. Factory option. Not user swappable.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.



Getac (UK) Ltd.

Getac House, Stafford Park 12, Telford,  
Shropshire TF3 3BJ, United Kingdom  
Tel : +44 (0) 1952 207 222  
Sales-Getac-UK@getac.com |  
www.getac.com/en/

Copyright © 2025 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.  
Information provided herewith is for reference only,available specification shall be subjected to quotation by request.