Getac



ZX70-EX FULLY RUGGED TABLET

- Qualcomm[®] Snapdragon™ 660, Octa-core Processor
- Verified as Android enterprise recommended ¹
- 7" LumiBond display with Getac sunlight readable technology and glove-enabled capacitive touchscreen
- 6ft drop, MIL-STD-810H and IP67 certified
- Optional barcode reader, RFID reader
- ATEX & IECEx explosive atmosphere certified















Power button
Optional: Contactless
HF RFID/NFC combo reader
8MP webcam

12MP rear camera
Optional: 1D/2D
imager barcode reader

MicroSD card slot
Optional: SIM card slot x 1
(Micro-SIM, 3FF)

Volume control button
Barcode launch button
USB host
Micro USB client

DC in Jack

SPECIFICATIONS

Operating System

Android™ 10.0

Mobile Computing Platform

Qualcomm[®] Snapdragon[™] 660, Octa-core 1.95GHz Max. 2.2GHz

VGA Controller

Qualcomm® Adreno™ 512 GPU

Display

7" Wide Viewing Angle TFT LCD HD (1280 x 720) Anti-static protection film LumiBond display with Getac sunlight readable technology Capacitive multi-touch screen

Storage & Memory

4GB LPDDR4 64GB eMMC

Keyboard

Power button 3 tablet programmable buttons

Pointing Device

Touchscreen - Capacitive multi-touch screen

Expansion Slot

Optional: 1D/2D imager barcode reader

I/O Interface

8M pixels webcam x 1
12M pixels autofocus rear camera x 1
DC in Jack x 1
USB 2.0 (Host) x 1
MicroUSB 2.0 (Client) x 1
MicroSD x 1
Optional: SIM card slot x 1 (Micro-SIM, 3FF)

Communication Interface

Wi-Fi 802.11ac Bluetooth (v5.0) ^{II} Dedicated GPS Optional: 4G LTE mobile broadband ^{III}

Security Feature

Optional: HF RFID/NFC combo reader iv, v

Power

AC adapter (25W, 100-240VAC, 50/60Hz) Li-ion battery (3.8V, typical 8480mAh; min. 8220mAh)

Dimension (W x D x H) & Weigh

218 x 142 x 27mm (8.58" x 5.6" x 1.08") 774g (1.71lbs) ^{vi}

Rugged Feature

MIL-STD-810H certified IP67 certified Vibration & 6ft (1.8m) drop resistant vii ATEX & IECEx certified

Environmental Specification

Temperature :
- Operating: -21°C to 60°C / -6°F to 140°F
- Storage: -40°C to 71°C / -40°F to 160°F

Humidity: - 95% RH, non-condensing

Explosion Protection

ATEX/IECEx Zone 2/22 Ex II 3G Ex ic op is IIC T5 Gc Ex II 3D Ex ic op is IIIB T100°C Dc

Pre-installed Software

Getac File Browser
Getac Camera
Getac Lamera
Getac Lamera
Getac Lamera
Getac Driving Safety Utility (trial version)
Getac Driving Safety Utility (trial version)
Getac deployXpress (trial version)
Getac settings and Google applications (Search, Chrome,
Gmail, Maps, YouTube, Play, Drive, YouTube music,
Play movies, Duo and photos)

Optional software

Getac Driving Safety Utility Getac deployXpress Getac OEMConfig

Accessories

AC adapter (25W; 12V/2A, 100-240VAC; 50/60H2)
Capacitive stylus with tether Pen holder
Wrist strap

Uptional:AC adapter (25W; 12V/2A, 100-240VAC; 50/60Hz)
Capacitive stylus with tether
Hand strap with stylus holder
Wrist strap
Pen holder

Bumper-to-Bumper warranty

Bumper-to-Bumper warranty
Accidents can take your equipment out of service
when you least expect it, especially in a rugged
environment, which can cause costly equipment
downtime.
That is why Getac has introduced accidental
damage as standard under our
Bumper-to-Bumper warranty, to help minimize
your enterprise IT costs.
Bumper-to-Bumper is your hassle-free guarantee.
That means you can depend on us to have your
unit back in service within days.

3 years Bumper-to-Bumper

ZX70-EX FULLY **RUGGED TABLET**

- Android enterprise recommended rugged devices deliver a consistent set of features verified by Google with an elevated device baseline, increased security standards and enterprise-focused features and behaviors to meet the needs of users. Google and Android are trademarks of Google LLC.
 Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- Units with 4G LTE option comes with an embedded SIM card slot.
- Card Sidt.

 13.56MHz HF RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).

 HF RFID/NFC combo reader applies to US & EU.

 Weight and dimensions vary from configurations and optional accessories.
- optional accessories.

 VII. Drop test results vary from configurations and optional
- accessories. VIII. Tested by an independent third-party test lab following MIL-STD-810H.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.





GETAC TECHNOLOGY CORPORATION

5F, Building A, No. 209, Section 1, Nangang Rd., Nangang Dist., Taipei City, 115018, Taiwan, R.O.C. Tel: +886 2 2785 7888 globalmarketing@getac.com | www.getac.com

Copyright © 2023 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only, available specification shall be subjected to quotation by request.