




V120 FULLY RUGGED LAPTOP

- Pronto per l'AI con i più recenti processori Intel® Core™ Ultra (Serie 2) e la tecnologia Intel® AI Boost
- Schermo da 12,2" FHD LumiBond con tecnologia Getac per la lettura sotto la luce del sole (1.000 nits) e touchscreen capacitivo
- Opzioni I/O versatili, tra cui fino a due Thunderbolt™ 4 e soluzioni docking
- Tecnologia LifeSupport per la sostituzione delle batterie
- Lettore Barcode 1D/2D Imager e batterie ad alta capacità opzionali
- Wi-Fi 7 offre velocità di trasferimento dati superiore



SPECIFICATIONS

Generation

G1

Operating System

Windows 11 Pro

Mobile Computing Platform

Intel® Core™ Ultra 5 processor 225H
Max. 4.9GHz with Intel® Turbo Boost Technology
- 18MB Intel® Smart Cache

Platform options:

Intel® Core™ Ultra 5 processor 235H, vPro® Enterprise
Max. 5.0GHz with Intel® Turbo Boost Technology
- 18MB Intel® Smart Cache

Intel® Core™ Ultra 7 processor 255H
Max. 5.1GHz with Intel® Turbo Boost Technology
- 24MB Intel® Smart Cache

Intel® Core™ Ultra 7 processor 265H, vPro® Enterprise
Max. 5.3GHz with Intel® Turbo Boost Technology
- 24MB Intel® Smart Cache

Graphics

Intel® Arc™ 130V GPU (For Intel® Core™ Ultra 5 processor) ⁱ
Intel® Arc™ 140V GPU (For Intel® Core™ Ultra 7 processor) ⁱ

NPU

Intel® AI Boost

Display

12.2" Wide Viewing Angle TFT LCD WUXGA (1920 x 1200)
Protection film
1,000 nits LumiBond display with
Getac sunlight readable technology
Capacitive multi-touch screen

Storage & Memory

16GB DDR5
Optional: 32GB / 64GB DDR5

256GB PCIe NVMe SSD
Optional: 512GB / 1TB / 2TB PCIe NVMe SSD

Keyboard

LED backlit membrane keyboard
Power button
4 programmable buttons

Pointing Device

Touchscreen
- Capacitive multi-touch screen
- Optional: Dual mode touchscreen (multi-touch and digitizer)
Touchpad
- Glide touchpad with left-click and right-click buttons

Audio

Integrated stereo speakers
Integrated dual-array microphone

Expansion Slot

Optional: Smart card reader
Optional: 1D/2D imager barcode reader ⁱⁱ
Optional: USB 3.2 Gen 2 Type-A + Serial port (9-pin; D-sub) ⁱⁱⁱ
Optional: USB 3.2 Gen 2 Type-A + MicroSD ⁱⁱ

I/O Interface

5MP webcam x 1 ⁱⁱⁱ
Audio in/out combo x 1
DC in Jack x 1
USB 3.2 Gen 2 Type-A x 2
Thunderbolt™ 4 Type-C x 2
LAN (RJ45) x 1
HDMI 2.0 x 1
Docking connector x 1
Optional: SIM card slot x 1 (Nano-SIM, 4FF) ^{iv,v}
Optional: Windows Hello face-authentication
5MP camera (front-facing) x 1 ⁱⁱⁱ
Optional: Tri RF antenna pass-through
for 4G (GPS, WLAN, WWAN)
Optional: Quad RF antenna pass-through
for 5G (GPS, WLAN, WWAN, WWAN MIMO)
Optional: 13MP auto focus rear camera x 1

Communication Interface

10/100/1000 base-T Ethernet
Intel® Wi-Fi 7 BE200, 802.11be
Bluetooth (v5.4) ^{vi}
Optional: Dedicated GPS with L1/L5 ^{vii}
Optional: 4G LTE mobile broadband with integrated GPS ^{ix}
Optional: 5G Sub-6 with integrated GPS ^{ix,viii}
Optional: Dual SIM (Nano-SIM 4FF and e-SIM) ^{iv,v}

Security Feature

TPM 2.0
Kensington lock
Smart card reader
Optional: Intel® vPro® Technology
Optional: Fingerprint reader
Optional: HF RFID reader ^{ix}
Optional: Windows Hello face-authentication
5MP camera (front-facing) ⁱⁱⁱ
Optional: Absolute Persistence®

Power

AC adapter (65W, 100-240VAC, 50/60Hz)
Li-ion battery (7.74V, typical 4070mAh; min. 3800mAh) x 2
LifeSupport battery swappable technology
Optional: High-capacity Li-ion battery
(11.61V, typical 4070mAh; min. 3800mAh) x 2

Dimension (W x D x H) & Weight

302 x 224 x 35.7mm (11.89" x 8.82" x 1.41")
2.1kg (4.63lbs) ^v

Rugged Feature

MIL-STD-810H certified
IP66 certified
MIL-STD-461G certified ^{xi}
Vibration 8.4ft (1.2m) drop resistant ^{xii}
- Operating: -29°C to 63°C / -20°F to 145°F
- Storage: -51°C to 71°C / -60°F to 160°F
Humidity:
- 95% RH, non-condensing

Environmental Specification

Temperature ^{xiv}
- Operating: -29°C to 63°C / -20°F to 145°F
- Storage: -51°C to 71°C / -60°F to 160°F
Humidity:
- 95% RH, non-condensing

Pre-installed Software

Getac Utility
Getac Camera
Getac Geolocation
Getac Barcode Manager ^{xv}
Optional: Absolute Secure Endpoint
Optional: Absolute Secure Access

Optional software

Getac Driving Safety Utility
Getac Monitoring
Getac VGPS Utility ^{xvi}

Accessories

Battery (7.74V, typical 4070mAh; min. 3800mAh)
AC adapter (65W, 100-240VAC)

Optional:

Carry bag
Battery (7.74V, typical 4070mAh; min. 3800mAh)
High-capacity Li-ion battery
(11.61V, typical 4070mAh; min. 3800mAh)
Multi-Bay charger (Dual-Bay)
Multi-Bay charger (Eight-Bay)
AC adapter (65W, 100-240VAC)
MIL-STD-461 AC adapter (90W, 100-240VAC)
DC-DC vehicle adapter (120W, 11-32VDC)
Digitizer pen
Capacitive stylus with tether
Protection film
Handle
Hard handle
Hand strap
Shoulder strap (2-point)
Vehicle cradle ^{xvii}
Vehicle dock ^{xviii}
Spare SSD kit
65W Type-C adapter
100W Type-C adapter
Getac rugged keyboard
Getac DS100 USB-C docking station with AC adapter

V120 FULLY RUGGED LAPTOP

Bumper-to-Bumper warranty

Gli imprevisti possono compromettere l'utilizzo dei dispositivi e causare costosi tempi di inattività. Ecco perché Getac ha introdotto la copertura dei danni accidentali come standard della garanzia Bumper-to-Bumper, consentendo una migliore gestione dei costi legati all'IT. Bumper-to-Bumper è la garanzia senza problemi. Questo significa che potete contare su di noi affinché il vostro dispositivo sia nuovamente operativo nel giro di pochi giorni.

Standard

3 anni Bumper-to-Bumper

- I. Units equipped with 16GB and dual channel memory come with Intel® Arc™ Graphics.
- II. Optional USB 3.2 Gen 2 Type-A + Serial port (9-pin; D-sub), optional USB 3.2 Gen 2 Type-A + Micro SD card reader, and optional 1D/2D imager barcode reader are mutually exclusive.
- III. 5MP webcam and optional Windows Hello face-authentication 5MP camera (front-facing) are mutually exclusive options.
- IV. Units with 4G/5G LTE option come with an embedded SIM card slot.
- V. One physical SIM card slot and one eSIM. Network service may vary depending on local telecommunication providers.
- VI. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- VII. Support GPS, GLONASS, Galileo, BeiDou and QZSS.
- VIII. Only available in the US, UK, EU, Australia and New Zealand.
- IX. 13.56MHz contactless HF RFID reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- X. Weight and dimensions vary from configurations and optional accessories.
- XI. MIL-STD-461 90W AC adapter sold separately.
- XII. Drop test results vary from configurations and optional accessories.
- XIII. Available with limited configurations and environment conditions.
- XIV. Tested by an independent third-party test lab following MIL-STD-810H.
- XV. Available when the barcode reader option is selected.
- XVI. Models require either embedded or standalone GPS module.
- XVII. Gamber-Johnson and Havis vehicle docks are e-mark certified.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

Vehicle Dock	
Serial Port	2
External VGA	1
Microphone	1
Audio Output	1
DC in Jack	1
USB	4
LAN	1
HDMI	1
RF Antenna Connector	3 (WWAN, WLAN, GPS)

Getac

GETAC TECHNOLOGY CORPORATION

Via Paracelso 26, Centro Direzionale Colleoni,
Palazzo Cassiopea 3 20864 Agrate Brianza (MB)
Tel: +39 039 8901584

Sales-getac-Italy@getac.com | www.getac.com/it/

Copyright © 2026 Getac Technology Corporation
and/or any of its affiliates. All Rights Reserved.
Information provided herewith is for reference
only, available specification shall be subjected to
quotation by request.