




X600 Pro-PCI FULLY RUGGED LAPTOP

- Processore Intel® Core™ i9 / i7 / i5 vPro® di 11° generazione
- Schermo da 15,6" FHD LumiBond con tecnologia Getac leggibile alla luce del sole (1.000 nits) e opzione touchscreen capacitivo
- Caratteristiche di sicurezza aziendale migliorate con TPM 2.0, blocco Kensington, triplo storage sostituibile dall'utente e lettore di smart card
- Connettività I/O versatile che include Thunderbolt™ 4
- Quattro batterie hot swappable



X600 Pro-PCI 3D demo



SPECIFICATIONS

Operating System

Windows 11 Pro

Mobile Computing Platform

Intel® Core™ i5-11500HE vPro® Processor
Max. 4.5GHz with Intel® Turbo Boost Technology
- 12MB Intel® Smart Cache

Platform options:

Intel® Core™ i7-11850HE vPro® Processor
Max. 4.7GHz with Intel® Turbo Boost Technology
- 24MB Intel® Smart Cache

Intel® Xeon® W-11865MRE vPro® Processor
Max. 4.7GHz with Intel® Turbo Boost Technology
- 24 MB Intel® Smart Cache

Graphics

Intel® UHD Graphics
Optional: NVIDIA® GeForce®
GTX1650 4GB discrete graphics controller ^{i,ii}

Display

15.6" TFT LCD FHD (1920 x 1080)
Protection film
1,000 nits LumiBond display with
Getac sunlight readable technology
Optional: Capacitive multi-touch screen

Storage & Memory

16GB DDR4
Optional: 32GB / 64GB / 128GB DDR4

512GB PCIe SSD
Optional: 1TB / 2TB PCIe SSD
Optional ^{2nd} storage: 512GB / 1TB / 2TB PCIe SSD
Optional ^{3rd} storage: 512GB / 1TB / 2TB PCIe SSD

Keyboard

LED backlit membrane keyboard
with integrated numeric keypad

Pointing Device

Touchscreen
- Optional: Capacitive multi-touch screen touchpad
- Touchpad with two buttons

Expansion Slot

Smart card reader
ExpressCard 54 + PCMCIA Type II
PCI or PCI-Express 3.0 expansion unit
(x2 slots) ^{iii,iv,v}
Optional: 2nd ExpressCard 54 or 2nd
PCMCIA Type II ^{vi}
Optional: SD card reader

Multimedia Bay

DVD super multi drive ^{vii}
Optional: Blu-Ray super multi drive ^{vii}

I/O Interface

5MP webcam x 1
Thunderbolt™ 4 Type-C x 1 ^{xvi}
USB 3.2 Gen 2 Type-A x 4
LAN (RJ-45) x 2
Audio in/out combo x 1
DC in Jack x 1
HDMI 2.0 x 1
Display port x 1
Serial port (9-pin; D-sub) x 2
External VGA (15-pin; D-sub) x1
or 3rd serial port (9-pin; D-sub) x 1 ^{viii}
Optional: SIM card slot x 1 (Mini-SIM, 2FF) ^{ix}

Communication Interface

2.5GBASE-T Ethernet
Intel® Wi-Fi 6E AX210, 802.11ax
Bluetooth (v5.2) ^x
Optional: Dedicated GPS ^{xi}
Optional: 4G LTE mobile broadband
with integrated GPS ^{ix,xi}

Security Feature

TPM 2.0
Kensington lock
Smart card reader
Intel® vPro® Technology
Getac Disk Wipe
Optional: Absolute Secure Access

Power

AC adapter (230W, 100-240VAC, 50/60Hz)
Battery (10.8V, typical 6900mAh;
min. 6600mAh) x 4

Dimension (W x D x H) & Weight

412 x 322 x 108.8mm (16.22" x 12.68" x 4.28") ^{xii}
8.145kg (17.95 lbs) ^{xii}

Rugged Feature

MIL-STD-810H certified
IP66 certified
MIL-STD-461G certified ^{xi}
Vibration and 3ft (0.9m) drop resistant

Environmental Specification

Temperature ^{xv} :
- Operating: -29°C to 63°C / -20°F to 145°F
- Storage: -51°C to 71°C / -60°F to 160°F
Humidity:
- 95% RH, non-condensing

Pre-installed Software

Getac Utility
Getac Geolocation
Optional: Absolute Secure Endpoint
Optional: Absolute Secure Access

Optional software

Getac Device Monitoring System (GDMS)

Accessories

Battery (10.8V, typical 6900mAh; min. 6600mAh) x 4
AC adapter (230W, 100-240VAC, 50/60Hz)
Capacitive stylus with tether

Optional:

Backpack
Battery (10.8V, typical 6900mAh; min. 6600mAh)
Multi-Bay charger (Dual-Bay)
Multimedia bay DVD super multi drive ^{vii}
Multimedia bay Blu-Ray super multi drive ^{vii}
AC adapter (230W, 100-240VAC, 50/60Hz)
MIL-STD-461 AC adapter (230W, 100-240VAC) ^{xiii}
DC-DC vehicle adapter (230W, 11-32VDC)
Capacitive stylus with tether
Protection film
Spare SSD kit

Bumper-to-Bumper warranty

Gli imprevisti possono compromettere l'utilizzo dei dispositivi e causare costosi tempi di inattività. Ecco perché Getac ha introdotto la copertura dei danni accidentali come standard della garanzia Bumper-to-Bumper, consentendo una migliore gestione dei costi legati all'IT. Bumper-to-Bumper è la garanzia senza problemi. Questo significa che potete contare su di noi affinché il vostro dispositivo sia nuovamente operativo nel giro di pochi giorni.

Standard

3 anni Bumper-to-Bumper

X600 Pro-PCI FULLY RUGGED LAPTOP

- I. The configuration with a discrete graphic controller requires the 230W AC adapter.
- II. 150W AC adaptor is not applicable with discrete graphic controller nor office dock.
- III. PCI or PCI-Express expansion unit is not compatible with vehicle dock nor office dock.
- IV. The PCI or PCI-Express expansion unit is not compatible with NVIDIA® Quadro RTX3000.
- V. PCI and PCI-E slots are mutually exclusive options.
- VI. The 2nd ExpressCard 54 and the 2nd PCMCIA Type II card readers are mutually exclusive.
- VII. DVD super multi drive and Blu-Ray super multi drive are mutually exclusive.
- VIII. The 3rdSerial port is optional and mutually exclusive with External VGA.
- IX. Units with 4G LTE option comes with an embedded SIM card slot.
- X. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- XI. Dedicated GPS and 4G LTE are mutually exclusive options.
- XII. Weight and dimensions vary from configurations and optional accessories.
- XIII. MIL-STD-461 230W AC adapter sold separately.
- XIV. X600 Pro-PCI can withstand 3ft (0.9m) drop in packaging.
- XV. Tested by an independent third-party test lab following MIL-STD-810H.
- XVI. Does not support USB power delivery.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.



GETAC TECHNOLOGY CORPORATION

Via Paracelso 26, Centro Direzionale Colleoni,
Palazzo Cassiopea 3 20864 Agrate Brianza (MB)
Tel: +39 039 8901584

Sales-getac-Italy@getac.com | www.getac.com/it/
Copyright © 2025 Getac Technology Corporation
and/or any of its affiliates. All Rights Reserved.
Information provided herewith is for reference
only,available specification shall be subjected to
quotation by request.