



IP66

K120 FULLY RUGGED TABLET

- 11th Generation Intel[®] Core[™] i7 / i5 vPro[™] Processor
- 12.5" FHD LumiBond[®] 2.0 Display with Getac Sunlight Readable Technology (1,200 nits) and Capacitive Touchscreen
- Enhanced Enterprise Security with optional Intel vPro, Windows Hello face-authentication camera, and multi-factor authentication options
- Multi-mode usage streamlined by extensive accessory selections
- LifeSupport[™] Battery Swappable Technology
- Thunderbolt[™] 4 brings lightning speed and performance



Rugged Mobile Computing Solutions

Specifications

Operating System Windows 10 Pro

Mobile Computing Platform Intel[®] Core[™] i5-1135G7 Processor Max. 4.2GHz with Intel[®] Turbo Boost Technology - 8MB Intel[®] Smart Cache

- oriviant Cache Platform Options: Intel® Core™ i5-1145G7 vPro™ Processor Max. 4.4GHz with Intel® Turbo Boost Technology - 8MB Intel® Smart Cache Intel® Core™ i7-1165G7 Processor Max. 4.7GHz with Intel® Turbo Boost Technology - 12MB Intel® Smart Cache

Intel® Core™ i7-1185G7 vPro™ Processor Max. 4.8GHz with Intel® Turbo Boost Technology - 12MB Intel® Smart Cache

VGA Controller Intel[®] Iris[®] Xe Graphics

Display

12.5" IPS TFT LCD FHD (1920 x 1080) Protection film 1200 nits LumiBond® display with Getac sunlight readable Capacitive multi-touch screen

Storage & Memory 16GB DDR4

Optional: 32GB DDR4 256GB PCIe NVMe SSD Optional: 512GB / 1TB PCIe NVMe SSD

Keyboard

Power button 5 tablet programmable buttons **Pointing Device**

Touchscreen

Capacitive multi-touch screen Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slot

Optional: 1D/2D imager barcode reader Optional: Serial port (9-pin; D-sub), or USB 2.0 port I/O Interface

Tablet

FHD webcam x 1⁺ 8M pixels auto focus rear camera x 1 8M pixels auto focus rear camera x 1 Headphone out/Mic-in Combo x 1 DC in Jack x 1 USB 3.2 Gen 2 Type-A x 1 Thunderbolt™ 4 x 1 LAN (RJ-45) x 1 HDMI x 1 Docking Connector x 2 Optional: Windows Hello face-authentication camera (front-facing) x 1[⊥] Optional: RF antenna pass-through for GPS, WLAN and WWAN Optional Keyboard Dock:

Optional Keyboard Dock:

DC in Jack x 1 USB 3.2 Gen 1 Type-A x 3 LAN (RJ45) x 1 HDMI x 1 Display Port 1.2 x 1 Serial port (9-pin; D-sub) x 1 Optional: RF antenna pass-through for GPS, WLAN and WWAN

Communication Interface 10/100/1000 base-T Ethernet Intel® Wi-Fi 6 AX201, 802.11ax Bluetooth (v5.2) ⁱⁱ Optional: Dedicated GPS ⁱⁱⁱ Optional: 46 LTE mobile broadband with integrated GPS ⁱⁱⁱ **Security Feature**

TPM 2.0

Kensington Lock Optional: Intel® vPro™ Technology Optional: Smart Card reader or HF RFID reader [™], [™] or fingerprint reader [™]

Power

AC Adapter (90W, 100-240VAC, 50/60Hz) Li-lon smart battery (11.1V, typical 2100mAh; min. 2040mAh) x 2 LifeSupport[™] battery swappable technology Optional: High capacity battery (14.4V, typical 3450mAh; min. 3300mAh) x 2

Dimension (W x D x H) & Weight

Tablet 329.5 x 238 x 24mm (12.97" x 9.37" x 0.94") 1.7kg (3.75lbs) ^{vii}

Tablet + Optional Keyboard Dock: 340.5 x 307.5 x 47mm (13.40" x 12.10" x 1.85") 3.13kg (6.9lbs) ^{vii}

Rugged Feature MIL-STD-810H certified

MIL-51D-51OH Cettilied IP66 certified MIL-STD-461G certified^{is} Vibration & 6 feet (1.8m) drop resistant ^{ix, x} e-Mark certified for vehicle usage Optional: ANSI / UL 121201, CSA C22.2 NO. 213 ^{sc}

Environmental Specification

Temperature *

- Operating: -29°C to 63°C / -20°F to 145°F - Storage: -51°C to 71°C / -60°F to 160°F Humidity: - 95% RH, non-condensing

Pre-installed Software

Getac Utility Getac Camera Getac Geolocation Getac Barcode Manager ^{xii} Optional: Absolute Persistence®

Accessories Battery (11.1V, typical 2100mAh; min. 2040mAh) AC Adapter (90W, 100-240VAC) Capacitive Stylus

Optional: Carry Bag Battery (11.1V, typical 2100mAh; min. 2040mAh) High Capacity Battery (14.4V, typical 3450mAh; min. 3300mAh) Multi-Bay Charger (Dual Bay) Multi-Bay Charger (Dual Bay) AC Adapter (90W, 100-240VAC) Office Dock AC Adapter (120W, 100-240VAC) MIL-STD-461 Certified AC Adapter (90W, 115-230VAC) Vehicle Adapter (120W, 11-32VDC) Diatizer Pen Optional: Digitizer Pen Capacitive Stylus Protection Film Tablet Hard Handle Hand Strap Shoulder Strap (2-point) Shoulder Harness (4-point; handsfree) Keyboard Dock Vehicle Dock Office Dock Spare SSD Kit

Bumper-to-Bumper Warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days. Standard

3 years Bumper-to-Bumper

FHD webcam and optional Windows Hello face-authentication camera (front-facing) are mutually exclusive options

- Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- Dedicated GPS is mutually exclusive with 4G LTE mobile broadband. Supports GPS and Glonass 13.56MHz Contactless HF RFID / NFC reader
- (ISO 15693, 14443 A/B, Mifare and FeliCa" compliant)
- LF/HF RFID reader option is not Energy Star 8.0 compliant Smart card reader, HF RFID reader and fingerprint
- scanner are mutually exclusive options.
- vii Weight and dimensions vary from configurations and optional accessories
- optional high capacity batteries add approx. 11 mm (H), 0.20 kg. viii MIL-STD-461G 90W AC adapter sold separately.
- Drop test results vary from configurations and optional accessories. ix
- Tested by an independent third-party test lab following MIL-STD-810H. Available with limited configurations.
- xii Available when barcode reader option is selected.

K120 Fully Rugged **Tablet**



Docking Solutions

	Vehicle Dock for Tablet Mode	Vehicle Dock for Laptop Mode	Office Dock for Tablet Mode	Office Dock for Laptop Mode
Serial Port	1	1	1	1
VGA	1	1	1	1
Microphone			1	1
Audio Output			1	1
DC in Jack	1	1	1	1
USB	USB 2.0 x 3 USB 3.2 Gen1 x 3	USB 2.0 x 3 USB 3.2 Gen1 x 3	USB 2.0 x 2 USB 3.2 Gen1 x 3	USB 2.0 x 2 USB 3.2 Gen1 x 3
LAN	2	2	2	2
HDMI	1	1	1	1
RF Antenna Connector	3 (WWAN, WLAN, GPS)	3 (WWAN, WLAN, GPS)		
Kensington Lock	1	1	1	1



GETAC TECHNOLOGY CORPORATION 5F, Building A, No. 209, Section 1, Nangang Rd., Nangang Dist., Taipei City, 11568, Taiwan, R.O.C. Tel : +886 2 2785 7888 globalmarketing@getac.com | www.getac.com



Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved ation provided herewith is for reference only available specification shall be subjected to quotation by request. V01M05Y21WW