



Dro

# UX10 FULLY RUGGED TABLET

- 10th Generation Intel<sup>®</sup> Core<sup>™</sup> i7 / i5 Processor
- 10.1" FHD LumiBond<sup>®</sup> 2.0 display with Getac sunlight readable technology (1,000 nits) and capacitive touchscreen
- Enhanced enterprise security with optional Intel vPro, Windows Hello face-authentication camera and multi-factor authentication options
- Detachable keyboard & multi-funtional hard handle for on-the-job flexibility
- Multiple configurable options to fit diverse usage scenarios



### Rugged Mobile Computing Solutions

### **Specifications**

#### **Operating System** Windows 10 Pro

#### **Mobile Computing Platform**

Intel<sup>®</sup> Core™ i5-10210U Processor 1.6GHz Max. 4.2GHz with Intel® Turbo Boost Technology - 6MB Intel<sup>®</sup> Smart Cache

Platform Options: Intel® Core™ i5-10310U vPro™ processor 1.7GHz Max. 4.4GHz with Intel® Turbo Boost Technology 6MB Intel<sup>®</sup> Smart Cache

Intel® Core™ i7-10510U Processor 1.8GHz Max. 4.9GHz with Intel® Turbo Boost Technology - 8MB Intel® Smart Cache

Intel<sup>®</sup> Core<sup>™</sup> i7-10610U vPro<sup>™</sup> processor 1.8GHz Max. 4.9GHz with Intel<sup>®</sup> Turbo Boost Technology - 8MB Intel<sup>®</sup> Smart Cache

#### VGA Controller

Intel<sup>®</sup> UHD Graphics Display 10.1" IPS TFT LCD FHD (1920 x 1200) Protection film

1000 nits LumiBond<sup>®</sup> display with Getac sunlight readable technology Capacitive multi-touch screen

#### Storage & Memory 8GB DDR4

Optional: 16GB / 32GB DDR4 256GB PCIe NVMe SSD Optional: 512GB / 1TB PCIe NVMe SSD

**Keyboard** 

Power button 5 tablet programmable buttons

#### **Pointing Device**

Touchscreen · Capacitive multi-touch screen · Optional: Dual mode touchscreen (multi-touch

and digitizer)

#### **Expansion Slot**

Optional (top side): 1D/2D imager barcode reader<sup>i</sup>, or serial port, or USB 3.2 Gen 1 Type-A, or USB 3.2 Gen 1 Type-C port, or LAN port (RJ-45), or VGA port<sup>ii</sup>, or HF RFID reader. Optional (right side): Fingerprint reader, or serial port+LAN port (RJ-45), or HF RFID reader <sup>w</sup> Optional (back side): Smart card reader, or bridge battery, or bridge battery+smart card reader

#### I/O Interface

FHD webcam x 1 8M pixels auto focus rear camera x 1 Audio in/out combo x 1 DC in Jack x 1 USB 3.2 Gen 2 Type-A x 1 HDML x 1 Docking Connector x 1 Optional: Windows Hello face-authentication camera (front-facing) x 1 \* Optional: RF antenna pass-through for GPS, WLAN and WWAN

#### **Communication Interface**

Intel® Wi-Fi 6 AX200, 802.11ax Bluetooth (v5.2) vi Optional: Dedicated GPS iii Optional: 4G LTE mobile broadband with integrated GPS Optional: 10/100/1000 base-T Ethernet

**Security Feature** 

#### TPM 2.0

Kensington Lock Optional: Intel<sup>®</sup> vPro™ Technology Optional: HF RFID reader Optional: Fingerprint reader <sup>iv</sup> Optional: Smart card reader <sup>iv</sup>

#### **Power**

AC Adapter (65W, 100-240VAC, 50/60 Hz) Li-Ion smart battery (11.1V, typical 4200mAh; min. 4080mAh) x 1 Optional: High capacity battery (10.8V, 9240mAh) x 1 Optional: Bridge battery  $^{\rm v}$ 

Dimension (W x D x H) & Weight 276.8 x 194.5 x 23.5mm (10.89" x 7.65" x 0.92") 1.22kg (2.68 lbs) <sup>vii</sup>

#### **Rugged Feature**

MIL-STD-810H certified IP65 certified MIL-STD-461G certified viii Vibration & 6 feet (1.8m) drop resistant <sup>icx</sup> e-Mark certified for vehicle usage Optional: ANSI / UL 121201, CSA C22.2 NO. 213 Optional: Salt fog certified

#### **Environmental Specification**

Temperature - Operating: -29°C to 63°C / -20°F to 145°F - Storage: -51°C to 71°C / -60°F to 160°F Humidity

95% RH, non-condensing

#### **Pre-installed Software** Getac Utility

Getac Camera Getac Geolocation Getac Barcode Manager <sup>xii</sup> Optional: Absolute Persistence®

#### Accessories

Battery (11.1V, typical 4200mAh; min. 4080mAh) AC Adapter (65W, 100-240VAC) Capacitive stylus with tether

#### **Optional:**

Carry Bag

Carry Bag Folio Case Battery (11.1V, typical 4200mAh; min. 4080mAh) High capacity Battery (10.8V, 9240 mAh) Multi-Bay Charger (Dual Bay) Multi-Bay Charger (Eight-Bay) AC Adapter (65W, 100-240VAC) Office Dock AC Adapter (90W, 100-240VAC) MIL-STD-461G Certified AC Adapter (90W, 100-240VAC) 100-240VAC) Vehicle Adapter (120W, 11-32VDC) Digitizer Pen Capacitive stylus with tether Protection Film Hand Strap Shoulder Strap (2-point) Shoulder Harness (4-point; handsfree) Detachable Keyboard Vehicle Dock Office Dock 100W Type-C Adapter

#### **Bumper-to-Bumper Warranty**

## Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment

downtime. That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your

#### unit back in service within days. Standard

3 years Bumper-to-Bumper

- 13.56MHz Contactless HF RFID reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant). 1D/2D imager barcode reader, HF RFID reader, serial port, LAN port (R/45), USB 3.2 Gen 1 Type-A, USB 3.2 Gen 1 Type-C por and VGA port are mutually exclusive options. Supports GPS and Gionass.
- Fingerprint scanner, HE RFID reader, and serial port+LAN port (RH5) are mutually exclusive options. Smart card reader, bridge battery and bridge battery+smart card reader are mutually iv
- exclusive options.
- Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of optime Dluetooth unified environment of active Bluetooth wireless devices that is
- operating in the area. vii Weight and dimensions vary from
- configurations and optional accessories. viii MIL-STD-461 90W AC adapter sold separately. ix Drop test results vary from configurations and
- optional accessories. Tested by an independent third-party test lab following MIL-STD-810H. FHD webcam and optional Windows Hello
- face-authentication camera (front-facing) are
- mutually exclusive options. xii Available when barcode reader option is selected.

## Fully Rugged **Tablet**



#### **Docking Solutions**

|                      | Vehicle Dock                    | Office Dock                     |
|----------------------|---------------------------------|---------------------------------|
| Serial Port          | 1                               | 1                               |
| VGA                  |                                 | 1                               |
| Microphone           |                                 | 1                               |
| Audio Output         |                                 | 1                               |
| DC in Jack           | 1                               | 1                               |
| USB                  | USB 2.0 x 2<br>USB 3.2 Gen1 x 2 | USB 2.0 x 2<br>USB 3.2 Gen1 x 2 |
| LAN                  | 1                               | 1                               |
| HDMI                 |                                 | 1                               |
| RF antenna Connector | 3 (WWAN,<br>WLAN, GPS)          |                                 |
| Kensington Lock      | 1                               | 1                               |



#### GETAC TECHNOLOGY CORPORATION

5F, Building A, No. 209, Section 1, Nangang Rd., Nangang Dist., Taipei City, 11568, Taiwan, R.O.C. Tel : +886 2 2785 7888 globalmarketing@getac.com | www.getac.com



Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved tion provided herewith is for reference only available specification shall be subjected to quotation by request. V02M06Y21WW