



UX10 FULLY RUGGED TABLET

- 10th Generation Intel[®] Core[™] i7 / i5 Processor
- 10.1" FHD LumiBond[®] 2.0 display with Getac sunlight readable technology (1,000 nits) and capacitive touchscreen
- Enhanced enterprise security with optional Intel vPro, Windows Hello face-authentication camera and multi-factor authentication options
- Detachable keyboard & multi-funtional hard handle for on-the-job flexibility
- Multiple configurable options to fit diverse usage scenarios



CERTIFIED WILLSTD UP65 6000 EXECTOR

Rugged Mobile Computing Solutions

Specifications

Generation G2

Operating System Windows 10 Pro

Mobile Computing Platform

Intel® Core™ i5-10210U Processor 1.6GHz Max. 4.2GHz with Intel® Turbo Boost Technology - 6MB Intel® Smart Cache

Platform options: Intel® Core™ J5-10310U vPro™ Processor 1.7GHz Max. 4.4GHz with Intel® Turbo Boost Technology - 6MB Intel® Smart Cache

Intel[®] Core™ i7-10510U Processor 1.8GHz Max. 4.9GHz with Intel[®] Turbo Boost Technology - 8MB Intel[®] Smart Cache

Intel[®] Core™ i7-10610U vPro™ Processor 1.8GHz Max. 4.9GHz with Intel® Turbo Boost Technology - 8MB Intel® Smart Cache

VGA Controller

Intel[®] UHD Graphics

Display

10.1" IPS TFT LCD FHD (1920 x 1200) Protection film 1,000 nits LumiBond[®] display with Getac sunlight readable technology Capacitive multi-touch screen

Storage & Memory

8GB DDR4 Optional: 16GB / 32GB DDR4 256GB PCIe NVMe SSD Optional: 512GB / 1TB PCIe NVMe SSD

Kevboard

Power button 5 tablet programmable buttons **Pointing Device**

Touchscreen

- Capacitive multi-touch screen - Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slot

Deptional (top side): 1D/2D imager barcode reader, or Serial port, or USB 3.2 Gen 1 Type-A port, or USB 3.2 Gen 1 Type-C port, or LAN port (RJ45), or VGA port', or HF RFID reader ^a Optional (right side): Fingerprint reader, or Serial port + LAN port (RJ45) ^a, or HF RFID reader ^a Optional (back side): Smart card reader, or Bridge battery, or Bridge battery + Smart card reader ^b

I/O Interface

FHD webcam x 1 ° 8M pixels auto focus rear camera x 1 Audio in/out combo x 1 DC in Jack x 1 USB 3.2 Gen 2 Type-A x 1 HDMI x 1 Docking connector x 1 Optional: Windows Hello face-authentication camera (front-facing) x 1 ° Optional: RF antenna pass-through for GPS, WWAN and WLAN

Communication Interface

Intel[®] Wi-Fi 6 AX200, 802.11ax Bluetooth (v5.2) ^{vi} Optional: Dedicated GPS vii

Optional: 4G LTE mobile broadband with integrated GPS vii Optional: 10/100/1000 base-T Ethernet

Security Feature

TPM 2.0

- Kensington lock Optional: Intel[®] vPro™ Technology Optional: HF RFID reader [∎] Optional: Fingerprint reader
- Optional: Smart card reader

Power

AC adapter (65W, 100-240VAC, 50/60 Hz) Li-ion smart battery (11.1V, typical 4200mAh; min. 4080mAh) x 1 Optional; High capacity battery (10.8V, 9240mAh) x 1 Optional: Bridge battery

Dimension (W x D x H) & Weight 276.8 x 194.5 x 23.5mm (10.89" x 7.65" x 0.92")

1.22kg (2.68lbs) ^{vii}

Rugged Feature MIL-STD-810H certified IP65 certified IP65 certified * MIL-STD-461G certified * Vibration & 6ft (1.8m) drop resistant * e-Mark certified for vehicle usage Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D) Context I, Cold for constituted Optional: Salt fog certified

Environmental Specification

Temperature ³ - Operating: -29°C to 63°C / -20°F to 145°F - Storage: -51°C to 71°C / -60°F to 160°F Humidity

- 95% RH, non-condensing **Pre-installed Software**

Getac Utility Getac Camera

Getac Geolocation Getac Barcode Manager ^{xii} Optional: Absolute Persistence®

Accessories

Battery (11.1V, typical 4200mAh; min. 4080mAh) AC adapter (65W, 100-240VAC) Capacitive stylus with tether

Optional:

Carry bag

Carry bag Folio case Battery (11.1V, typical 4200mAh; min. 4080mAh) High capacity battery (10.8V, 9240 mAh) Multi-Bay charger (Dual-Bay) Multi-Bay charger (Eight-Bay) AC adapter (65W, 100-240VAC) Office dock AC adapter (90W, 100-240VAC) MIL-STD-461G certified AC adapter (90W, 100-240VAC) 100-240VAC) Vehicle adapter (120W, 11-32VDC) Digitizer pen Capacitive stylus with tether Protection film Hand strap Shoulder strap (2-point) Shoulder harness (4-point; handsfree) Detachable keyboard Vehicle dock Office dock

100W Type-C adapter **Bumper-to-Bumper Warranty**

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment

downtime That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

- 1D/2D imager barcode reader, Serial port, USB 3.2 Gen 1 Type-A port, USB 3.2 Gen 1 Type-C port, LAN port (RJ45) and VGA port are mutually exclusive options. 13.56MHz contactless HF RFID reader (ISO 15693, 14443 A/B, Mifare and FeliCa[™] compliant)
- compliant).
- Fingerprint scanner, HF RFID reader and Serial port + LAN port (RJ45) are mutually exclusive iii
- options. Smart card reader, Bridge battery and Bridge battery + Smart card reader are mutually iv exclusive options.
- FHD webcam and optional Windows Hello face-authentication camera (front-facing) are
- mutually exclusive options. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area. vii Supports GPS and Glonass. viii Weight and dimensions vary from

- configurations and optional accessories. MIL-STD-461 90W AC adapter sold separately. Drop test results vary from configurations and ix
- optional accessories. Tested by an independent third-party test lab following MIL-STD-810H. xii Available when barcode reader option is
- selected

Fully Rugged **Tablet**



Docking Solutions

	Vehicle Dock	Office Dock
Serial Port	1	1
VGA		1
Microphone		1
Audio Output		1
DC in Jack	1	1
USB	USB 2.0 x 2 USB 3.2 Gen1 x 2	USB 2.0 x 2 USB 3.2 Gen1 x 2
LAN	1	1
HDMI		1
RF Antenna Connector	3 (WWAN, WLAN, GPS)	
Kensington Lock	1	1



Getac (UK) Ltd.

Getac House, Stafford Park 12, Telford, Shropshire TF3 3BJ, United Kingdom Tel : +44 (0) 1952 207 222 Sales-Getac-UK@getac.com | en.getac.com



Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved tion provided herewith is for reference only available specification shall be subjected to quotation by request. V01M07Y21UK

