



F110-EX FULLY RUGGED TABLET

- Certificazione ATEX / IECEx per atmosfere potenzialmente esplosive
- Sicurezza aziendale avanzata con TPM 2.0 ed opzioni Intel vPro e Windows Hello-Authentication camera
- Processore Intel® Core™ i7 / i5 di 8° generazione
- Display da 11,6 pollici LumiBond® 2.0 dotato di tecnologia Getac, con leggibilità anche alla luce diretta del sole e touch screen capacitivo
- Lettore Barcode 1D / 2D Imager e lettore LF / HF RFID opzionali



Specifications

Generation

G5

Operating System

Windows 10 Pro

Mobile Computing Platform

Intel® Core™ i5-8265U Processor 1.6GHz
Max. 3.9GHz with Intel® Turbo Boost Technology
- 6MB Intel® Smart Cache

Platform options:

Intel® Core™ i5-8365U vPro™ Processor 1.6GHz
Max. 4.1GHz with Intel® Turbo Boost Technology
- 6MB Intel® Smart Cache

Intel® Core™ i7-8565U Processor 1.8GHz
Max. 4.6GHz with Intel® Turbo Boost Technology
- 8MB Intel® Smart Cache

Intel® Core™ i7-8665U vPro™ Processor 1.9GHz
Max. 4.8GHz with Intel® Turbo Boost Technology
- 8MB Intel® Smart Cache

VGA Controller

Intel® UHD Graphics

Display

11.6" IPS TFT LCD FHD (1920 x 1080)

Protection film

800 nits LumiBond® display with Getac sunlight

readable technology

Capacitive multi-touch screen

Storage & Memory

8GB DDR4

Optional: 16GB / 32GB DDR4

256GB SATA SSD

Optional: 512GB / 1TB SATA SSD

Optional: 256GB / 512GB / 1TB PCIe NVMe SSD

Keyboard

Power button

5 tablet programmable buttons

Pointing Device

Touchscreen

- Capacitive multi-touch screen

- Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slot

Optional: 1D/2D imager barcode reader

I/O Interface

FHD webcam x 1ⁱ

8M pixels auto focus rear camera x 1

Audio in/out combo x 1

DC in Jack x 1

USB 3.2 Gen 2 Type-A x 1

HDMI x 1

Optional: Windows Hello face-authentication camera (front-facing) x 1ⁱ

Communication Interface

Intel® Dual Band Wireless-AC 9260, 802.11ac

Bluetooth (v5.1)ⁱⁱ

Optional: Dedicated GPS

Optional: 4G LTE mobile broadband

Security Feature

TPM 2.0

Kensington lock

Optional: Intel® vPro™ Technology

Optional: LF/HF RFID reader^{iii,iv}, or HF RFID reader^v

Power

AC adapter (65W, 100-240VAC, 50/60Hz)

Li-ion smart battery (11.4V, typical 2160mAh;

min. 2100mAh) x 2

Dimension (W x D x H) & Weight

314 x 207 x 24.5mm (12.4" x 8.15" x 0.96")

1.49kg (3.28lbs)^{vi}

Rugged Feature

MIL-STD-810H certified

IP65 certified

Vibration & 4ft (1.2m) drop resistant^{vii}

ATEX & IECEx certified

Environmental Specification

Temperature^{viii}:

- Operating: -21°C to 60°C / -6°F to 140°F

- Storage: -51°C to 71°C / -60°F to 160°F

Humidity:

- 95% RH, non-condensing

Explosion Protection

ATEX/IECEx Zone 2/22

Ex II 3G Ex ic op is IIC T4 Gc

Ex II 3D Ex ic op is IIIB T130°C Dc

Pre-installed Software

Getac Utility

Getac Camera

Getac Geolocation

Getac Barcode Manager^x

Optional: Absolute Persistence[®]

Accessories

Battery (11.4V, typical 2160mAh; min. 2100mAh)

AC adapter (65W, 100-240VAC)

Capacitive stylus with tether

Optional:

Battery (11.4V, typical 2160mAh; min. 2100mAh)

AC adapter (65W, 100-240VAC)

Digitizer pen

Capacitive stylus with tether

Protection film

Hand strap

Shoulder strap (2-point)

Shoulder harness (4-point; handsfree)

Garanzia Bumper-to-Bumper

Gli imprevisti possono compromettere l'utilizzo dei dispositivi e causare tempi di inattività.

Ecco perché Getac ha introdotto la copertura dei danni accidentali come elemento standard della Garanzia totale Bumper-to-Bumper, consentendo una migliore gestione dei costi legati all'IT.

La Garanzia totale è una formula agevole che offre il servizio di logistica Pack & Collect e garantisce un servizio di assistenza e riparazione rapido, effettuato da personale qualificato di Getac e di una riconsegna altrettanto veloce.

In questo modo il dispositivo sarà nuovamente operativo nel giro di pochi giorni.

Standard

3 anni Garanzia totale Bumper-to-Bumper

- i FHD webcam and optional Windows Hello face-authentication camera (front-facing) are mutually exclusive options.
- ii Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- iii LF(125kHz)/HF(13.56MHz) combo RFID/NFC reader (iClass, HID Prox, ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- iv LF/HF RFID reader option is not Energy Star 8.0 compliant.
- v 13.56MHz HF RFID reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- vi Weight and dimensions vary from configurations and optional accessories.
- vii Drop test results vary from configurations and optional accessories.
- viii Tested by an independent third-party test lab following MIL-STD-810H.
- ix Available when barcode reader option is selected.

F110-EX

Fully Rugged Tablet



Getac

GETAC ITALIA

Via Parcelso 26, Centro Direzionale Colleoni,
Palazzo Cassiopea 3 20864 Agrate Brianza (MB)

Tel: +39 039 8901584

Sales-getac-Italy@getac.com | www.getac.com/it/



Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.
Le informazioni riportate sono puramente indicative.
Le specifiche disponibili sono da verificare al momento dell'offerta. V01M09Y21IT