



F110 FULLY RUGGED TABLET

- Processore Intel® Core™ i7 / i5 vPro™ di 11° generazione
- Thunderbolt™ 4 offre velocità e prestazioni straordinarie
- Sicurezza potenziata con tecnologia Intel® vPro™ opzionale, crittografia del disco Windows, TPM 2.0 e numerose altre modalità di autenticazione multifattoriale opzionali
- Configurazioni opzionali in base alle diverse esigenze, a scelta: lettore codici a barre 1D/2D imager / porta USB 2.0 / porta seriale + LAN
- Tecnologia di sostituzione della batteria LifeSupport™



Detachable keyboard



Specifiche tecniche

Generation

G6

Operating System

Windows 10 Pro

Mobile Computing Platform

Intel® Core™ i5-1135G7 Processor
Max. 4.2GHz with Intel® Turbo Boost Technology
- 8MB Intel® Smart Cache

Platform options:

Intel® Core™ i5-1145G7 vPro™ Processor
Max. 4.4GHz with Intel® Turbo Boost Technology
- 8MB Intel® Smart Cache

Intel® Core™ i7-1165G7 Processor
Max. 4.7GHz with Intel® Turbo Boost Technology
- 12MB Intel® Smart Cache

Intel® Core™ i7-1185G7 vPro™ Processor
Max. 4.8GHz with Intel® Turbo Boost Technology
- 12MB Intel® Smart Cache

VGA Controller

Intel® Iris® Xe Graphics

Display

11.6" IPS TFT LCD FHD (1920 x 1080)
Protection film
1,000 nits LumiBond® display with Getac sunlight readable technology
Capacitive multi-touch screen

Storage & Memory

8GB DDR4
Optional: 16GB / 32GB DDR4
256GB PCIe NVMe SSD
Optional: 512GB / 1TB PCIe NVMe SSD

Keyboard

Power button
4 tablet programmable buttons

Pointing Device

Touchscreen
- Capacitive multi-touch screen
- Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slot

Optional: Smart card reader
Optional: 1D/2D imager barcode reader, or USB 2.0 port, or serial port + LAN (RJ45)¹
Optional²: HF RFID Reader, or Fingerprint Reader

I/O Interface

FHD webcam x 1ⁱⁱⁱ
8M pixels auto focus rear camera x 1
Audio in/out combo x 1
DC in Jack x 1
USB 3.2 Gen 2 Type-A x 1
Thunderbolt™ 4 Type-C x 1
Docking connector x 1
Optional: Windows Hello face-authentication camera (front-facing) x 1ⁱⁱⁱ
Optional: RF antenna pass-through for GPS, WWAN and WLAN

Communication Interface

Intel® Wi-Fi 6 AX201, 802.11ax
Bluetooth (v5.2)^{iv}
Optional: Dedicated GPS
Optional: 4G LTE mobile broadband with integrated GPS
Optional: 10/100/1000 base-T Ethernet i (Occupies expansion slot)

Security Feature

TPM 2.0
Kensington lock
Optional: Intel® vPro™ Technology
Optional: HF RFID Reader^{vi,ii}, or Smart Card Reader, or Fingerprint Readerⁱⁱ
Optional: Windows Hello face-authentication camera (front-facing) x 1ⁱⁱⁱ

Power

AC adapter (90W, 100-240VAC, 50/60Hz)
Li-ion smart battery (11.4V, typical 2680mAh; min. 2640mAh) x 2
LifeSupport™ battery swappable technology
Optional: High capacity battery (11.1V, typical 4200mAh; min. 4080mAh) x 2

Dimension (W x D x H) & Weight

314 x 207 x 25mm (12.4" x 8.15" x 0.98")
1.5kg (3.3lbs)^{viii}

Rugged Feature

MIL-STD-810H certified
IP66 certified
MIL-STD-461G certified^{viii}
Vibration & 6ft (1.8m) drop resistant
e-Mark certified for vehicle usage
Optional: ANSUL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D)^x

Environmental Specification

Temperature^{ix}:
- Operating: -29°C to 63°C / -20°F to 145°F
- Storage: -51°C to 71°C / -60°F to 160°F
Humidity:
- 95% RH, non-condensing

Pre-installed Software

Getac Utility
Getac Camera
Getac Geolocation
Getac Barcode Manager^v
Optional: Absolute Persistence®

Accessories

Battery (11.4V, typical 2680mAh; min. 2640mAh)
AC adapter (90W, 100-240VAC, 50/60Hz)
Capacitive stylus with tether

Optional:

Carry bag
Battery (11.4V, typical 2680mAh; min. 2640mAh)
High capacity battery (11.1V, typical 4200mAh; min. 4080mAh)
Multi-Bay charger (Dual-Bay)
Multi-Bay charger (Eight-Bay)
Detachable keyboard
AC adapter (90W, 100-240VAC, 50 / 60Hz)
Office dock AC adapter (90W, 100-240VAC)
MIL-STD-461 certified AC adapter (90W, 115-230VAC)
DC-DC vehicle adapter (120W, 11-32VDC)
Digitizer pen
Capacitive stylus with tether
Protection film
Tablet hard handle
Hand strap
Shoulder strap (2-point)
Shoulder harness (4-point; handsfree)
Vehicle cradle
Vehicle dock
Office dock
100W Type-C adapter

Garanzia Bumper-to-Bumper

Gli imprevisti possono compromettere l'utilizzo dei dispositivi e causare tempi di inattività.

Ecco perché Getac ha introdotto la copertura dei danni accidentali come elemento standard della Garanzia totale Bumper-to-Bumper, consentendo una migliore gestione dei costi legati all'IT.

La Garanzia totale è una formula agevole che offre il servizio di logistica Pack & Collect e garantisce un servizio di assistenza e riparazione rapido, effettuato da personale qualificato di Getac e di una riconsegna altrettanto veloce.

In questo modo il dispositivo sarà nuovamente operativo nel giro di pochi giorni.

Standard

3 anni Garanzia totale Bumper-to-Bumper

- i 1D/2D imager barcode reader, or USB (USB 2.0) port, or Serial port + LAN are mutually exclusive options.
- ii HF RFID reader and fingerprint reader are mutually exclusive options.
- iii FHD webcam and optional Windows Hello face-authentication camera (front-facing) are mutually exclusive options.
- iv Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- v Available when barcode reader option is selected.
- vi 13.56MHz HF RFID reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- vii Weight and dimensions vary from configurations and optional accessories; optional high-capacity batteries add approx. 6mm (H), 0.24kg.
- viii MIL-STD-461 90W AC adapter sold separately.
- ix Available with limited configurations.
- x Tested by an independent third-party test lab following MIL-STD-810H.

F110

Fully Rugged Tablet



Soluzioni dock

Dock per veicolo Dock per ufficio

| | Dock per veicolo | Dock per ufficio |
|---------------------------|---------------------|------------------|
| Porte seriali | 2 | 2 |
| VGA esterna | 1 | 1 |
| Microfono | 1 | 1 |
| Uscita audio | 1 | 1 |
| Ingresso Jack DC | 1 | 1 |
| Porte USB | 4 | 4 |
| LAN | 1 | 1 |
| HDMI | 1 | 1 |
| Connettore per Antenna RF | 3 (GPS, WWAN, WLAN) | -- |

Getac

GETAC ITALIA

Via Paracelso 26, Centro Direzionale Colleoni,
Palazzo Cassiopea 3 20864 Agrate Brianza (MB)
Tel: +39 039 8901584
Sales-getac-Italy@getac.com | www.getac.com/it/



Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.
Le informazioni riportate sono puramente indicative.
Le specifiche disponibili sono da verificare al momento dell'offerta. V01M09Y21IT