



T800 FULLY RUGGED TABLET

- Display da 8,1" HD LumiBond® 2.0, per una migliore visualizzazione
- Funzione brevettata Getac componenti aggiuntivi SnapBack: Lettore di Smart Card e lettore RFID contactless combinato o seconda batteria
- Scelta tra lettore di codici a barre 1D/2D imager, oppure porta seriale o Ethernet
- Certificato MIL-STD-810G e IP65
- Sicurezza aziendale aumentata con TPM2.0 e Windows Disk Encryption.



Office Dock



SnapBack add-on



Specifiche tecniche

Generation

G2

Operating System

Windows 10 Pro

Mobile Computing Platform

Intel® Atom Processor x7-Z8750 1.6GHz
Max. 2.56GHz
- 2MB Cache

VGA Controller

Intel® HD Graphics

Display

8.1" IPS TFT LCD WXGA (1280 x 800)
Protection film
600 nits LumiBond® display with Getac sunlight readable technology

Storage & Memory

4GB LPDDR3
Optional: 8GB LPDDR3
128GB eMMC
Optional: 256GB eMMC

Keyboard

Power button
5 tablet programmable buttons

Pointing Device

Touchscreen
- Capacitive multi-touch screen
- Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slot

Optional: 1D/2D imager barcode reader, Serial port, Ethernetⁱ
Optional: SnapBack add-on: Smart card and HF RFID/NFC reader comboⁱⁱ
Optional: SnapBack add-on: 2nd expanded batteryⁱⁱⁱ
Optional: SnapBack add-on: Smart card and magnetic stripe reader^{iv}
Optional: SnapBack add-on: Smart card and UHF RFID reader^v

I/O Interface

FHD webcam x 1
8M pixels auto focus rear camera x 1
Audio in/out combo x 1
DC in Jack x 1
USB 3.2 Gen 1 Type-A x 1
Micro HDMI x 1
Docking connector x 1
Optional: RF antenna pass-through for GPS, WWAN and WLAN

Communication Interface

Intel® Wi-Fi 6 AX200, 802.11ax
Bluetooth (v5.2)^{vi}
Optional: Dedicated GPS
Optional: 4G LTE mobile broadband
Optional: 10/100/1000 base-T Ethernet (Occupies expansion slot)

Security Feature

TPM 2.0
Optional: SnapBack add-on: Smart card and HF RFID/NFC combo reader^{iv}
Optional: SnapBack add-on: Smart card and magnetic stripe reader
Optional: SnapBack add-on: Smart card and UHF RFID reader^v

Power

AC adapter (65W, 100-240VAC, 50/60Hz)
Li-ion battery (7.4V, typical 4200mAh; min. 4080mAh)
LifeSupport™ battery swappable technology (only with SnapBack 2nd expanded battery)

Dimension (W x D x H) & Weight

227 x 151 x 24mm (8.93" x 5.94" x 0.94")
0.88kg (1.94lbs)^{vii}

Rugged Feature

MIL-STD-810H certified
IP65 certified
MIL-STD-461G certified
Vibration & 6ft (1.8m) drop resistant^{viii}
e-Mark certified for vehicle usage
Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D)^{ix}

Environmental Specification

Temperature^{ix}:
- Operating: -21°C to 50°C / -6°F to 122°F
- Storage: -51°C to 71°C / -60°F to 160°F
Humidity:
- 95% RH, non-condensing

Pre-installed Software

Getac Utility
Getac Camera
Getac Barcode Manager^x
Optional: Absolute Persistence®

Accessories

Battery (7.4V, typical 4200mAh; min. 4080mAh)
AC adapter (65W, 100-240VAC)
Capacitive stylus with tether

Optional:

Carry bag
Battery (7.4V, typical 4200mAh; min. 4080mAh)
2nd expanded battery (14.4V, 2100mAh)
Multi-Bay charger (Dual-Bay)
Multi-Bay expanded battery dock with adapter (Six-Bay)
Multi-Bay charger (Eight-Bay)
AC adapter (65W, 100-240VAC)
Office dock AC adapter (90W, 100-240VAC)
MIL-STD-461 certified AC adapter (90W, 115-230VAC)
DC-DC vehicle adapter (120W, 11-32VDC)
Digitizer pen
Capacitive stylus with tether
Protection film
Hand strap
Shoulder strap (2-point)
Wrist strap
Vehicle cradle
Vehicle dock
Office dock

Garanzia Bumper-to-Bumper

Gli imprevisti possono compromettere l'utilizzo dei dispositivi e causare tempi di inattività. Ecco perché Getac ha introdotto la copertura dei danni accidentali come elemento standard della Garanzia totale Bumper-to-Bumper, consentendo una migliore gestione dei costi legati all'IT.

La Garanzia totale è una formula agevole che offre il servizio di logistica Pack & Collect e garantisce un servizio di assistenza e riparazione rapido, effettuato da personale qualificato di Getac e di una riconsegna altrettanto veloce.

In questo modo il dispositivo sarà nuovamente operativo nel giro di pochi giorni.

Standard

3 anni Garanzia totale Bumper-to-Bumper

- i 1D/2D imager barcode reader, Serial port and Ethernet are mutually exclusive options.
- ii All snapBack add-ons are mutually exclusive options.
- iii Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- iv 13.56MHz HF RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- v US (902-928MHz, UHF RFID tags of EPC Class 1 Gen2 ISO18000-63 standards compliant) EU (865-868MHz, UHF RFID tags of EPC Class 1 Gen2 ISO18000-63 standards compliant) The maximum read distance of UHF RFID is determined by the design, size of individual tags and environments. Contacting local Getac sales representatives for test arrangements is highly recommended.
- vi Weight and dimensions vary from configurations and optional accessories.
- vii Drop test results vary from configurations and optional accessories.
- viii Available with limited configurations.
- ix Tested by an independent third-party test lab following MIL-STD-810H.
- x Available when barcode reader option is selected.

T800

Fully Rugged Tablet



Docking Solutions

	Vehicle Dock	Office Dock
Serial Port	1	--
External VGA	--	1
Microphone	1	1
Audio Output	1	1
DC in Jack	1	1
USB	2	4
LAN	1	1
HDMI	--	1
RF Antenna Connector	3 (WWAN, WLAN, GPS)	--

Getac

GETAC ITALIA

Via Paracelso 26, Centro Direzionale Colleoni,
Palazzo Cassiopea 3 20864 Agrate Brianza (MB)
Tel: +39 039 8901584
Sales-getac-Italy@getac.com | www.getac.com/it/



Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.
Le informazioni riportate sono puramente indicative,
Le specifiche disponibili sono da verificare al momento dell'offerta. V01M09Y21IT