



ZX70 FULLY RUGGED TABLET



- Qualcomm® Snapdragon™ 660, processore Octa_core
- Verificato come Android Enterprise Recommended¹
- Schermo Lumibond® da 7" con tecnologia Getac leggibile alla luce del sole e touchscreen capacitivo, utilizzabile con i guanti
- Certificato per cadute da 1,8 metri circa, MIL-STD-810H e IP67
- Optional: Lettore di codici a barre e lettore RFID
- GPS a elevata sensibilità



Office dock



Vehicle dock



Specifiche tecniche

Generation

G2

Operating System

Android™ 10.0

Mobile Computing Platform

Qualcomm® Snapdragon™ 660, Octa-core 1.95GHz
Max. 2.2GHz

VGA Controller

Qualcomm® Adreno™ 512 GPU

Display

7" IPS TFT LCD HD (1280 x 720)

Protection film

LumiBond® display with Getac sunlight readable technology

Capacitive multi-touch screen

Storage & Memory

4GB LPDDR4

64GB eMMC

Keyboard

Power button

3 tablet programmable buttons

Pointing Device

Touchscreen

- Capacitive multi-touch screen

Expansion Slot

Optional: 1D/2D imager barcode reader

I/O Interface

8M pixels webcam x 1

12M pixels auto focus rear camera x 1

DC in Jack x 1

USB 2.0 (Host) x 1

MicroUSB 2.0 (Client) x 1

MicroSD x 1

Docking connector (Pogo / JAE) x 1

Optional: RF antenna pass-through for GPS and WWAN

Communication Interface

Wi-Fi 802.11ac

Bluetooth (v5.0) ⁱⁱ

Dedicated GPS

Optional: 4G LTE mobile broadband

Security Feature

Optional: HF RFID/NFC combo reader ^{iii, iv}

Power

AC adapter (25W, 100-240VAC, 50/60Hz)

Li-ion battery (3.8V, typical 8480mAh; min. 8220mAh)

Dimension (W x D x H) & Weight

218 x 142 x 27mm (8.58" x 5.6" x 1.08")

762g (1.68lbs) ^v

Rugged Feature

MIL-STD-810H certified

IP67 certified

Vibration & 6ft (1.8m) drop resistant ^{vi}

Optional: ANSVUL 121201, CSA C22.2 NO. 213

(Class I, Division 2, Groups A, B, C, D)

Environmental Specification

Temperature ^{vii}:

- Operating: -21°C to 60°C / -6°F to 140°F

- Storage: -40°C to 71°C / -40°F to 160°F

Humidity:

- 95% RH, non-condensing

Pre-installed Software

Getac File Browser

Getac Camera

Getac Input Method

DeployeXpress Client

Getac settings and Google applications (Search, Chrome, Gmail, Maps, YouTube, Play, Drive, Play music, Play movies, Duo and photos)

Accessories

AC adapter (25W; 12V/2A, 100-240VAC; 50/60Hz)

Capacitive stylus with tether

Pen holder

Wrist strap

Optional:

Carry bag

AC adapter (25W; 12V/2A, 100-240VAC; 50/60Hz)

Office dock AC adapter (60W, 110-240VAC)

DC-DC vehicle adapter (120W, 11-32VDC)

Capacitive stylus with tether

Protection film

Shoulder strap (2-point)

Wrist strap

Rotating hand strap with kickstand and stylus holder

holder

USB to RS232 converter cable

Docking connector to HDMI converter cable

Vehicle dock

Office dock

Garanzia Bumper-to-Bumper

Gli imprevisti possono compromettere l'utilizzo dei dispositivi e causare tempi di inattività.

Ecco perché Getac ha introdotto la copertura dei danni accidentali come elemento standard della Garanzia totale Bumper-to-Bumper, consentendo una migliore gestione dei costi legati all'IT.

La Garanzia totale è una formula agevole che offre il servizio di logistica Pack & Collect e garantisce un servizio di assistenza e riparazione rapido, effettuato da personale qualificato di Getac e di una riconsegna altrettanto veloce.

In questo modo il dispositivo sarà nuovamente operativo nel giro di pochi giorni.

Standard

3 anni Garanzia totale Bumper-to-Bumper

- i Android enterprise recommended rugged devices deliver a consistent set of features verified by Google with an elevated device baseline, increased security standards and enterprise-focused features and behaviors to meet the needs of users. Google and Android are trademarks of Google LLC.
- ii Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- iii 13.56MHz contactless HF RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- iv HF RFID/NFC combo reader applies to US & EU.
- v Weight and dimensions vary from configurations and optional accessories.
- vi Drop test results vary from configurations and optional accessories.
- vii Tested by an independent third-party test lab following MIL-STD-810H.

ZX70

Fully Rugged Tablet



Docking Solutions

	Getac-made Vehicle Dock (JAE)	Havis Vehicle Dock (Pogo, power only)	Havis Vehicle Dock (JAE)	Gamber-Johnson Charging Cradle (Pogo)	Havis Vehicle Dock (Pogo)	Office Dock (JAE)	Office Dock (Pogo)
Serial Port	1	--	1	--	1	--	--
Speaker	1	--	--	--	--	--	--
Audio Output	1	1	1	--	1	1	1
DC in Jack	1	1	1	1	1	1	1
USB	USB Host x 2	--	USB2.0 x 2	--	USB2.0 x 2	USB Host x 2 MicroUSB Client x 1	USB Host x 2
LAN	1	--	1	--	1	1	1
HDMI	1	--	1	--	--	1	--
RF Antenna Connector	(WWAN, GPS)	(WWAN, GPS)	(WWAN, GPS)	--	(WWAN, GPS)	--	--

Getac

GETAC ITALIA

Via Parcelso 26, Centro Direzionale Colleoni,
Palazzo Cassiopea 3 20864 Agrate Brianza (MB)

Tel: +39 039 8901584

Sales-getac-Italy@getac.com | www.getac.com/it/



Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.
Le informazioni riportate sono puramente indicative,
Le specifiche disponibili sono da verificare al momento dell'offerta. V01M09Y21IT