Getac



B360 PRO FULLY RUGGED Notebook

- MIL-STD 810H, 6ft operating drop rating, IP66 certified and optional salt fog resistant
- 10th Generation Intel[®] Core[™] Processor
- 13.3" FHD LumiBond[®] 2.0 display with Getac sunlight readable technology (1,400 nits) and capacitive touchscreen
- Optional NVIDIA[®] GeForce[®] GTX1050 4GB discrete graphic controller
- Enhanced enterprise security with optional dual user replaceable storage, Windows Hello faceauthentication camera, integrated 1D/2D imager barcode reader and multi-factor authentication options
- LifeSupport[™] battery swappable technology





SPECIFICATIONS

Operating System	Windows 10 Pro	
Mobile Computing Platform	Intel [®] Core™ i5-10210U Processor 1.6GHz Max. 4.2GHz with Intel [®] Turbo Boost Technology - 6MB Intel [®] Smart Cache	
	Platform options:	
	Intel [®] Core™ i5-10310U vPro™ Processor 1.7GHz	
	Max. 4.4GHz with Intel [®] Turbo Boost Technology	
	- 6MB Intel [®] Smart Cache	
	Intel [®] Core™ i7-10510U Processor 1.8GHz	
	Max. 4.9GHz with Intel [®] Turbo Boost Technology	
	- 8MB Intel [®] Smart Cache	
	Intel [®] Core™ i7-10610U vPro™ Processor 1.8GHz	
	Max. 4.9GHz with Intel [®] Turbo Boost Technology	
	- 8MB Intel [®] Smart Cache	
	Intel [®] Core™ i7-10710U Processor 1.1GHz	
	Max. 4.7GHz with Intel [®] Turbo Boost Technology	
	12MB Intel [®] Smart Cache	
VGA Controller	Intel [®] UHD Graphics Optional: NVIDIA [®] GeForce [®] GTX1050 4GB discrete graphics controller ^{i,viii}	
Display	13.3" IPS TFT LCD FHD (1920 x 1080)	
	Protection film	
	1,400 nits LumiBond [®] display with Getac sunlightreadable technology	
Storage & Memory	8GB DDR4	
	Optional: 16GB / 32GB / 64GB DDR4	
	256GB PCIe NVMe SSD	
	Optional: 512GB / 1TB PCIe NVMe SSD	
	Optional 2 nd Storage ⁱⁱ : 256GB / 512GB / 1TB SATA SSD	
Kaubaard	LED harklik marshrana kashaard	
Keyboard	LED backlit membrane keyboard Optional: LED backlit rubber keyboard	
Expansion Slots	Smart card reader x 1	
	Optional: Discrete graphics controller, or PCMCIA Type II, or	
	ExpressCard/54	
	Optional: 1D/2D imager barcode reader	

Getac 02

Multimedia Bay	Optional: DVD super multi drive / Blu-Ray super multi drive $^{ m iii}$	
I/O Interface	FHD webcam x 1	
	Audio in/out combo x 1	
	DC in Jack x 1	
	PowerShare USB 2.0 x 1	
	USB 3.2 Gen 2 Type-A x 2	
	LAN (RJ45) x 1	
	HDMI x 1	
	Docking connector x 1	
	Optional: SIM card slot x 1 (Mini-SIM, 2FF)	
	Optional: Windows Hello face-authentication camera (front-	
	facing) x 1 Optional: RF antenna pass-through for GPS, WWAN and	
	WLAN	
	Configurable I/O options ^{iv} :	
	Serial port (9-pin; D-sub) x 1 + External VGA (15-pin; D-sub) x	
	1, or	
	Serial port (9-pin; D-sub) x 1 + USB 3.2 Gen 2 Type-C x 1, or	
	Serial port (9-pin; D-sub) x 1 + Display port x 1	
	Serial port (9-pin; D-sub) x 2 + External VGA (15-pin; D-sub) x	
	1, or	
	Serial port (9-pin; D-sub) x 2 + USB 3.2 Gen 2 Type-C x 1, or	
	Serial port (9-pin; D-sub) x 2 + Display port x 1	
Communication Interface	10 / 100 / 1000 base-T Ethernet	
	Intel [®] Wi-Fi 6 AX200, 802.11ax	
	Bluetooth (v5.2) ^v	
	Optional dedicated GPS ^{vi}	
	Optional: 4G LTE mobile broadband with integrated GPS vi,vii	
Pre-installed software	Getac Utility	
	Getac Geolocation	
	Getac Barcode Manager ^{xiii}	
	Optional: Absolute Persistence®	
Security Features	TPM 2.0	
	Kensington lock	
	Optional: HF RFID reader ^{viii}	
	Smart card reader	
Power	AC adapter (90W, 100-240VAC, 50/60Hz)	
	AC adapter (120W, 100-240VAC, 50/60Hz) ^{ix}	
	High Capacity Battery (10.8V, typical 6900mAh; min.6600mAh)	
	x 2	
	LifeSupport™ battery swappable technology	
Dimension (W x D x H) & Weigh	342 x 281 x 53.5mm (13.46" x 11.06" x 2.11")	
	3.08Kg (6.79lbs) [×]	

Rugged Feature	MIL-STD-810H certified IP66 certified MIL-STD-461G certified ^{xi} Vibration & 6ft (1.8m) drop resistant e-Mark certified for vehicle usage Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D) Optional: Salt fog certified	
Environmental Specification	Temperature ^{xii} : - Operating: -29°C to 63°C / -20°F to 145°F - Storage: -51°C to 71°C / -60°F to 160°F Humidity: - 95% RH, non-condensing	
Accessories	High capacity battery (10.8V, typical 6900mAh; min. 6600mAh) AC adapter (90W, 100-240VAC) Capacitive stylus with tether Optional: Backpack	
	High Capacity Battery (10.8V, typical 6900mAh; min. 6600mAh) Multi-Bay charger (Dual-Bay) Multi-Bay charger (Eight-Bay) AC adapter (90W, 100-240VAC) AC adapter ^{ix} (120W, 100-240VAC)	
	MIL-STD-461 certified AC adapter (90W, 115-230VAC) DC-DC vehicle adapter (120W, 11-32VDC) Capacitive stylus with tether Protection film	
	Vehicle cradle Vehicle dock Office dock Spare SSD kit 100W Type-C adapter ^{xiv}	
Bumper-to-Bumper warranty	Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime. That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.	
	Standard 3 years Bumper-to-Bumper	

I. Discrete graphics card, PCMCIA slot, and Expresscard slot are mutually exclusive.

II. Second storage is optional and will be fitted with a removable cover when not chosen at point of purchase.

- III. DVD super multi drive and Blu-Ray super multi drive are mutually exclusive.
- IV. External VGA, USB 3.2 Gen 2 Type-C port and Display port are mutually exclusive.
- V. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- VI. Dedicated GPS is mutually exclusive with 4G LTE mobile broadband.
- VII. Units with 4G LTE option comes with an embedded SIM card slot.
- VIII. HF(13.56MHz) combo HF RFID/NFC reader (iClass, HID Prox , ISO 15693, 14443 A/B, Mifare, and FeliCa™ compliant).
- IX. 120W AC adapter is used for office dock and for device configured with discrete graphics card.
- X. Weight and dimensions vary from configurations and optional accessories.
- XI. MIL-STD-461G 90W AC adapter sold separately.
- XII. Tested by an independent third-party test lab following MIL-STD-810H.
- XIII. Available when barcode reader option is selected.
- XIV. Do not support the configurations with discrete graphics card.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

	Vehicle Dock	Office Dock
Serial Port	2	2
External VGA	1	1
Microphone	1	1
Audio Output	1	1
DC in Jack	1	1
USB	6	5
LAN	2	2
HDMI	1	1
RF Antenna Connector	(GPS, WWAN, WLAN)	-

Getac (UK) Ltd.

Getac House, Stafford Park 12, Telford, Shropshire TF3 3BJ, United Kingdom Tel : +44 (0) 1952 207 222 Sales-Getac-UK@getac.com I www.getac.com/en/ Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only, available specification shall be subjected to quotation by request. V01M09Y21WW

05