





- 11th Generation Intel® Core™ i7 / i5 vPro™ Processor
- Thunderbolt™ 4 brings lightning speed and performance
- Enhanced enterprise security with optional Intel[®] vPro[™], Windows Hello face-authentication camera,
 TPM 2.0 and many more multi-factor authentication options
- Configurable options to fit diverse data collection needs: Optional 1D/2D imager barcode reader / USB 2.0 port / Serial port + LAN port (RJ45)
- LifeSupport™ battery swappable technology













SPECIFICATIONS

| Operating System | Windows 10 Pro |
|--|--|
| Mobile Computing Platform Options | Intel® Core™ i5-1135G7 Processor Max. 4.2GHz with Intel® Turbo Boost Technology - 8MB Intel® Smart Cache |
| | Platform options: |
| | Intel® Core™ i5-1145G7 vPro™ Processor |
| | Max. 4.4GHz with Intel® Turbo Boost Technology - 8MB Intel® Smart Cache |
| | Intel® Core™ i7-1165G7 Processor |
| | Max. 4.7GHz with Intel® Turbo Boost Technology - 12MB Intel® Smart Cache |
| | Intel® Core™ i7-1185G7 vPro™ Processor Max. 4.8GHz with Intel® Turbo Boost Technology |
| | - 12MB Intel® Smart Cache |
| VGA Controller | Intel® Iris® X® Graphics |
| Display | 11.6" IPS TFT LCD FHD (1920 x 1080) |
| | Protection film |
| | 1,000 nits LumiBond® display with Getac sunlight readable technology |
| | Capacitive multi-touch screen |
| Storage & Memory | 8GB DDR4 |
| , | Optional: 16GB / 32GB DDR4 |
| | 256GB PCIe NVMe SSD |
| | Optional: 512GB / 1TB / 2TB PCle NVMe SSD |
| Keyboard | Power button |
| | 4 tablet programmable buttons |
| Pointing Device | Touchscreen |
| | - Capacitive multi-touch screen |
| | - Optional: Dual mode touchscreen (multi-touch and digitizer) |
| Expansion Slots | Optional: Smart card reader |
| | Optional: 1D/2D imager barcode reader, or USB 2.0 port, or |
| | serial port + LAN (RJ45) |
| | Optional ": HF RFID Reader, or Fingerprint Reader |

I/O Interface FHD webcam x 1 "

8M pixels auto focus rear camera x 1

Audio in/out combo x 1

DC in Jack x 1

Thunderbolt™ 4 Type-C x 1 USB 3.2 Gen 2 Type-A x 1 Docking connector x 1

Optional: SIM card slot x 1 (Micro-SIM, 3FF)

Optional: Windows Hello face-authentication camera (front-

facing) x 1 iii

Optional: RF antenna pass-through for GPS, WWAN and

WLAN

Communication Interface Intel® Wi-Fi 6 AX201, 802.11ax

Bluetooth (v5.2) iv

Optional: Dedicated GPS

Optional: 4G LTE mobile broadband with integrated GPS $^{\rm v}$ Optional: 10/100/1000 base-T Ethernet $^{\rm i}$ (Occupies expansion

slot)

Pre-installed software Getac Utility

Getac Camera Getac Geolocation

Getac Barcode Manager ^{xi}
Optional: Absolute Persistence[®]

Security Features TPM 2.0

Kensington lock

Optional: Intel® vPro™ Technology

Optional: Windows Hello face-authentication camera (front-

facing) "

Optional: HF RFID Reader vi, ii, or Smart Card Reader, or

Fingerprint Reader "

Power AC adapter(90W,100-240VAC, 50/60Hz)

Li-ion smart battery(11.4V,typical 2680mAh;min. 2640mAh) x 2

 $Life Support^{\intercal M}\ battery\ swappable\ technology$

Optional: High capacity battery (11.1V, typical 4200mAh;

min.4080mAh) x 2

Dimension (W x D x H) & Weigh 314 x 207 x 25mm (12.4" x 8.15" x 0.98")

1.52kg (3.35lbs) vii

Rugged Features

MIL-STD-810H certified

IP66 certified

MIL-STD-461G certified viii

Vibration & 6ft (1.8m) drop resistant e-Mark certified for vehicle usage

Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division

2, Groups A, B, C, D) ix

Environmental Specifications

Temperature *:

- Operating: -29°C to 63°C / -20°F to 145°F

- Storage: -51°C to 71°C / -60°F to 160°F

Humidity:

- 95% RH, non-condensing

Accessories

Battery (11.4V, typical 2680mAh; min. 2640mAh)

AC adapter (90W, 100-240VAC, 50 / 60Hz)

Capacitive stylus with tether

Optional:

Carry bag

Battery (11.4V, typical 2680mAh; min. 2640mAh)

High capacity battery (11.1V, typical 4200mAh; min.4080mAh)

Multi-Bay charger (Dual-Bay) Multi-Bay charger (Eight-Bay)

AC adapter (90W, 100-240VAC, 50 / 60Hz)

Office dock AC adapter (90W, 100-240VAC)

MIL-STD-461 certified AC adapter (90W, 115-230VAC)

DC-DC vehicle adapter (120W, 11-32VDC)

Digitizer pen

Capacitive stylus with tether

Hand strap

Shoulder strap (2-point)

Shoulder harness (4-point; handsfree)

Detachable keyboard

Vehicle cradle

Vehicle dock

Office dock

100W Type-C adapter

Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee.

That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper



- I. 1D/2D imager barcode reader, or USB (USB 2.0) port, or Serial port + LAN are mutually exclusive options.
- II. HF RFID reader and fingerprint reader are mutually exclusive options.
- III. FHD webcam and optional Windows Hello face-authentication camera (front-facing) are mutually exclusive options.
- IV. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- V. Units with 4G LTE option comes with an embedded SIM card slot.
- VI. 13.56MHz HF RFID reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- VII. Weight and dimensions vary from configurations and optional accessories; optional high-capacity batteries add approx. 6mm (H), 0.24kg.
- VIII. MIL-STD-461 90W AC adapter sold separately.
- IX. Available with limited configurations.
- X. Tested by an independent third-party test lab following MIL-STD-810H.
- XI. Available when barcode reader option is selected.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

| | Vehicle Dock | Office Dock |
|----------------------|---------------------|-------------|
| Serial Port | 2 | 2 |
| External VGA | 1 | 1 |
| Microphone | 1 | 1 |
| Audio Output | 1 | 1 |
| DC in Jack | 1 | 1 |
| USB | 4 | 4 |
| LAN | 1 | 1 |
| HDMI | 1 | 1 |
| RF Antenna Connector | 3 (WWAN, WLAN, GPS) | - |

Getac USA

15495 Sand Canyon Ave. Suite 350

Irvine, CA 92618 Tel : 949-681-2900

GetacSales_US@getac.com I www.getac.com/us/

Copyright © 2022 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.

Information provided herewith is for reference only,

available specification shall be subjected to quotation by request.