





- Intel® Core™ i7-7820EQ Processor
- 15.6" TFT LCD FHD with Getac QuadraClear® sunlight readable display
- Optional NVIDIA® Quadro® P2000 4GB discrete graphics controller
- Multimedia bay & PCI/PCle 3.0 expansion unit











SPECIFICATIONS

Generation	G3	
Operating System	Windows 10 Pro	
Mobile Computing Platform	Intel [®] Core [™] i5-7440EQ 2.9GHz Max. 3.6GHz - 6MB Intel [®] Smart Cache	
	Platform options: Intel® Core™ i7-7820EQ 3.0GHz Max. 3.7GHz - 8MB Intel® Smart Cache	
VGA Controller	Intel® HD Graphics 630 Optional: NVIDIA® GeForce® GTX1050 4GB discrete graphics controller Optional: NVIDIA® Quadro® P2000 4GB discrete graphics controller	
Display	15.6" TFT LCD FHD (1920 x 1080) Protection film 1,000 nits QuadraClear® sunlight readable display Optional: Resistive touch screen	
Storage & Memory	8GB DDR4 Optional: 16GB / 32GB / 64GB DDR4 500GB SATA HDD / 512GB SATA SSD Optional: 1TB SATA HDD / 1TB / SSD	
Keyboard	LED backlit membrane keyboard with integrated numeric keypad Optional: LED backlit rubber keyboard	
Pointing Device	Touchscreen - Optional: Pressure sensitive touchscreen Touchpad - Touchpad with two buttons	



Smart card reader x 1 **Expansion Slots**

ExpressCard/54 x 1

Optional: PCMCIA Type II x 1

Multimedia Bay DVD super multi drive

Optional 2nd storage: 500GB HDD / 1TB HDD / 512GB SSD / 1TB

Optional 2nd battery: 10.8V, 9240mAh, 99.8Wh

I/O Interface Audio input (Mini-jack) x 1

Audio output (Mini-jack) x 1

DC in Jack x 1

USB 3.2 Gen 1 Type-A x 4

LAN (RJ45) x 2 HDMI 1.4 x 1

Docking connector x 1

External VGA (15-pin; D-sub) x 1 Serial port (9-pin; D-sub) x 2 Optional: FHD webcam x 1

Optional: RF antenna pass-through for GPS ", and WLAN

Communication Interface 10/100/1000 base-T Ethernet

Intel® Dual Band Wireless-AC 8265, 802.11ac

Bluetooth (v4.2) iii Optional: Dedicated GPS

Security Features TPM 2.0

> Kensington lock Intel[®] vPro™ Technology Smart card reader

Power AC adapter (150W, 100-240VAC, 50/60Hz)

Li-ion battery (10.8V, 9240mAh, 99.8Wh)

Optional: Multimedia bay 2nd Li-ion battery (10.8V, 9240mAh,

99.8Wh)

Dimension (W x D x H) & Weight 410 x 320 x 65mm (16.1" x 12.6" x 2.5")

5.2 kg (11.4 lbs) iv

Rugged Features MIL-STD-810H certified

IP65 certified

MIL-STD-461G certified ^v Vibration & drop resistant Full magnesium alloy case

Shock-protected removable HDD

Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division

2, Groups A, B, C, D) vi



Environmental Specifications

Temperature vii:

- Operating: -20°C to 55°C / -4°F to 131°F

- Storage: -40°C to 71°C / -40°F to 160°F

Humidity:

- 95% RH, non-condensing

Pre-installed Software

Getac Utility

Getac Geolocation

Optional: Absolute Persistence®

Optional software

Getac Device Monitoring System (GDMS)

Accessories

Battery (10.8V, 9240mAh, 99.8Wh) AC adapter (150W, 100-240VAC)

Optional:

Backpack

Battery (10.8V, 9240mAh, 99.8Wh)

Multimedia bay 2nd Storage

Multimedia bay 2nd battery (10.8V, 9240mAh, 99.8Wh)

Multi-Bay charger (Dual-Bay)

Multimedia bay DVD super multi drive

AC adapter (150W, 100-240VAC)

Office dock AC adapter (150W, 100-240VAC)

MIL-STD-461 AC adapter (150W, 100-240VAC)

Stylus with tether

Protection film

PCI or PCI-Express 3.0 expansion unit (x2 slots) viii

Vehicle dock vii

Office dock viii

Spare SSD kit

Bumper-to-Bumper Warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

5 years Bumper-to-Bumper



I. Share memory size may vary by different operating system and RAM size.

II. Optional RF antenna pass-through for GPS, PCI or PCI-Express expansion unit are mutually exclusive options.

III. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.

IV. Weight and dimensions vary from configurations and optional accessories. Depth including hard handle.

V. MIL-STD-461 150W AC adapter sold separately.

- VI. PCI or PCI-Express 3.0 expansion unit is not available with ANSI/UL 121201, CSA C22.2 NO. 213 configurations.
- VII. Tested by an independent third-party test lab following MIL-STD-810H.
- VIII. PCI or PCI-Express 3.0 expansion unit is not compatible with vehicle dock and office dock.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

	Vehicle Dock	Office Dock
Serial Port	2	1
External VGA	1	1
Microphone	1	1
Audio Output	1	1
DC in Jack	1	1
USB	USB 2.0 x 4	USB 3.0 x 2 USB 2.0 x 2
LAN	1	1
RF Antenna Connector	3 (optional)	-

GETAC TECHNOLOGY CORPORATION

Via Paracelso 26, Centro Direzionale Colleoni, Palazzo Cassiopea 3 20864 Agrate Brianza (MB)

Tel: +39 039 8901584

Sales-getac-Italy@getac.com I www.getac.com/it/

Copyright © 2022 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.

Le informazioni riportate sono puramente indicative,

Le specifiche disponibili sono da verificare al momento dell'offerta.