



X500 FULLY RUGGED Notebook

- Intel[®] Core[™] i7-7820EQ Processor
- 15.6" TFT LCD FHD with Getac QuadraClear® sunlight readable display
- Optional NVIDIA® Quadro® P2000 4GB discrete graphics controller
- Multimedia bay & PCI/PCIe 3.0 expansion unit





SPECIFICATIONS

Generation	G3	
Operating System	Windows 10 Pro	
Mobile Computing Platform	Intel [®] Core™ i5-7440EQ 2.9GHz Max. 3.6GHz - 6MB Intel [®] Smart Cache	
	Platform options: Intel [®] Core™ i7-7820EQ 3.0GHz Max. 3.7GHz - 8MB Intel [®] Smart Cache	
VGA Controller	Intel [®] HD Graphics 630 Optional: NVIDIA [®] GeForce [®] GTX1050 4GB discrete graphics controller Optional: NVIDIA [®] Quadro [®] P2000 4GB discrete graphics controller	
Display	15.6" TFT LCD FHD (1920 x 1080) Protection film 1,000 nits QuadraClear [®] sunlight readable display Optional: Resistive touch screen	
Storage & Memory	8GB DDR4 Optional: 16GB / 32GB / 64GB DDR4 ⁱ 500GB SATA HDD / 512GB SATA SSD Optional: 1TB SATA HDD / 1TB / SSD	
Keyboard	LED backlit membrane keyboard with integrated numeric keypad Optional: LED backlit rubber keyboard	
Pointing Device	Touchscreen - Optional: Pressure sensitive touchscreen Touchpad - Touchpad with two buttons	
Expansion Slots	Smart card reader x 1 ExpressCard/54 x 1 Optional: PCMCIA Type II x 1	

Multimedia Bay	DVD super multi drive Optional 2 nd storage: 500GB HDD / 1TB HDD / 512GB SSD / 1TB SSD Optional 2 nd battery: 10.8V, 9240mAh, 99.8Wh
I/O Interface	Audio input (Mini-jack) x 1 Audio output (Mini-jack) x 1 DC in Jack x 1 USB 3.2 Gen 1 Type-A x 4 LAN (RJ45) x 2 HDMI 1.4 x 1 Docking connector x 1 External VGA (15-pin; D-sub) x 1 Serial port (9-pin; D-sub) x 2 Optional: FHD webcam x 1 Optional: RF antenna pass-through for GPS ⁱⁱ , and WLAN
Communication Interface	10/100/1000 base-T Ethernet Intel® Dual Band Wireless-AC 8265, 802.11ac Bluetooth (v4.2) ⁱⁱⁱ Optional: Dedicated GPS
Security Features	TPM 2.0 Kensington lock Intel® vPro™ Technology Smart card reader
Power	AC adapter (150W, 100-240VAC, 50/60Hz) Li-ion battery (10.8V, 9240mAh, 99.8Wh) Optional: Multimedia bay 2 nd Li-ion battery (10.8V, 9240mAh, 99.8Wh)
Dimension (W x D x H) & Weight	410 x 320 x 65mm (16.1" x 12.6" x 2.5") 5.2 kg (11.4 lbs) [™]
Rugged Features	MIL-STD-810H certified IP65 certified MIL-STD-461G certified ^v Vibration & drop resistant Full magnesium alloy case Shock-protected removable HDD Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D) ^{vi}

Environmental Specifications	Temperature ^{vii} : - Operating: -20°C to 55°C / -4°F to 131°F - Storage: -40°C to 71°C / -40°F to 160°F Humidity: - 95% RH, non-condensing
Pre-installed Software	Getac Utility Getac Geolocation Optional: Absolute Persistence [®]
Optional software	Getac Device Monitoring System (GDMS)
Accessories	Battery (10.8V, 9240mAh, 99.8Wh) AC adapter (150W, 100-240VAC)
	Optional: Backpack Battery (10.8V, 9240mAh, 99.8Wh) Multimedia bay 2 nd Storage Multimedia bay 2 nd battery (10.8V, 9240mAh, 99.8Wh) Multi-Bay charger (Dual-Bay) Multimedia bay DVD super multi drive AC adapter (150W, 100-240VAC) Office dock AC adapter (150W, 100-240VAC) MIL-STD-461 AC adapter (150W, 100-240VAC) Stylus with tether Protection film PCI or PCI-Express 3.0 expansion unit (x2 slots) ^{viii} Vehicle dock ^{viii} Office dock ^{viii} Spare SSD kit
Bumper-to-Bumper Warranty	Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime. That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days. Standard
	5 years Bumper-to-Bumper

I. Share memory size may vary by different operating system and RAM size.

II. Optional RF antenna pass-through for GPS, PCI or PCI-Express expansion unit are mutually exclusive options.

III. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.

IV. Weight and dimensions vary from configurations and optional accessories. Depth including hard handle.

V. MIL-STD-461 150W AC adapter sold separately.

VI. PCI or PCI-Express 3.0 expansion unit is not available with ANSI/UL 121201, CSA C22.2 NO. 213 configurations.

VII. Tested by an independent third-party test lab following MIL-STD-810H.

VIII. PCI or PCI-Express 3.0 expansion unit is not compatible with vehicle dock and office dock.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

	Vehicle Dock	Office Dock
Serial Port	2	1
External VGA	1	1
Microphone	1	1
Audio Output	1	1
DC in Jack	1	1
USB	USB 2.0 x 4	USB 3.0 x 2 USB 2.0 x 2
LAN	1	1
RF Antenna Connector	3 (optional)	-

Getac (UK) Ltd.

Getac House, Stafford Park 12, Telford, Shropshire TF3 3BJ, United Kingdom Tel : +44 (0) 1952 207 222 Sales-Getac-UK@getac.com I www.getac.com/en/ Copyright © 2022 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only, available specification shall be subjected to quotation by request.