




# X600 PRO FULLY Rugged Notebook

- 11th Generation Intel<sup>®</sup> Core™ i9 / i7 / i5 vPro™ Processor
- 15.6" FHD LumiBond<sup>®</sup> display with Getac sunlight readable technology (1,000 nits) and optional capacitive touchscreen
- Enhanced enterprise security features with TPM 2.0, Kensington lock, triple user-replaceable storage and Smart card reader
- Versatile I/Os connectivity including Thunderbolt™ 4 and docking solutions
- Optional discrete graphic NVIDIA® Quadro® RTX3000
- Expandable modules for additional ports, batteries, DVD super multi drive, and connectivity





### **SPECIFICATIONS**

Operating System	Windows 11 Pro	
Mobile Computing Platform	Intel <sup>®</sup> Core™ i5-11500H vPro™ Processor Max. 4.6GHz with Intel <sup>®</sup> Turbo Boost Technology - 12MB Intel <sup>®</sup> Smart Cache	
	Platform options:	
	Intel <sup>®</sup> Core™ i7-11850H vPro™ Processor Max. 4.8GHz with Intel <sup>®</sup> Turbo Boost Technology	
	- 24MB Intel <sup>®</sup> Smart Cache	
	Intel <sup>®</sup> Core™ i9-11950H vPro™ Processor	
	Max. 4.9GHz with Intel <sup>®</sup> Turbo Boost Technology - 24MB Intel <sup>®</sup> Smart Cache	
VGA Controller	Intel <sup>®</sup> UHD Graphics	
	Optional: NVIDIA <sup>®</sup> Quadro <sup>®</sup> RTX3000 6GB discrete graphics controller <sup>i</sup>	
Display	15.6" TFT LCD FHD (1920 x 1080)	
	Protection film	
	1,000 nits LumiBond <sup>®</sup> display with Getac sunlight readable technology	
	Optional: Capacitive multi-touch screen	
Storage & Memory	16GB DDR4	
	Optional: 32GB / 64GB / 128GB DDR4 512GB PCIe SSD	
	Optional: 1TB / 2TB PCIe SSD	
	Optional 2nd storage: 512GB / 1TB / 2TB PCIe SSD	
	Optional 3rd storage: 512GB / 1TB / 2TB PCIe SSD	
Keyboard	LED backlit membrane keyboard with integrated numeric keypad	
Pointing Device	Touchscreen	
	- Optional: Capacitive multi-touch screen	
	Touchpad - Touchpad with two buttons	
Expansion Slot	Smart card reader	
	ExpressCard 54 + PCMCIA Type II	
	Optional: 2nd ExpressCard 54 or 2nd PCMCIA Type II <sup>II</sup> Optional: SD card reader	

Multimedia Bay	Multimedia bay battery (11.1V, typical 4200mAh; min. 3980mAh) DVD super multi drive <sup>III</sup> Optional: Multimedia bay 2nd battery (11.1V, typical 4200mAh; min. 3980mAh) or Blu-Ray super multi drive <sup>III</sup>
I/O Interface	FHD webcam x 1
	Audio in/out combo x 1
	DC in Jack x 1
	USB 3.2 Gen 2 Type-A x 4
	Thunderbolt™ 4 Type-C x 1
	LAN (RJ45) x 2
	HDMI 2.0 x 1
	Display port x 1
	Docking connector x 1
	External VGA (15-pin; D-sub) x 1 or 3rd Serial port (9-pin; D-
	sub) x 1 <sup>iv</sup>
	Serial port (9-pin; D-sub) x 2
	Optional: SIM card slot x 1 (Mini-SIM, 2FF) $^{ m v}$
	Optional: RF antenna pass-through for GPS, WWAN and
	WLAN
Communication	2.5GBASE-T Ethernet
	Intel <sup>®</sup> Wi-Fi 6E AX210, 802.11ax
	Bluetooth (v5.2) <sup>vi</sup>
	Optional: Dedicated GPS <sup>vii</sup>
	Optional: 4G LTE mobile broadband with integrated GPS $^{v, vii}$
Security Feature	TPM 2.0
	Kensington lock
	Smart card reader
	Intel <sup>®</sup> vPro™ Technology
Power	AC adapter (230W, 100-240VAC, 50/60Hz) <sup>i</sup>
rowei	Battery (10.8V, typical 6900mAh; min. 6600mAh) x 2
	Multimedia bay battery (11.1V, typical 4200mAh; min.
	3980mAh) x 1
	Optional: Multimedia bay 2nd battery (11.1V, typical
	4200mAh; min. 3980mAh) <sup>III</sup>
Dimension (W x D x H) & Weight	412 x 322 x 77.4mm (16.22" x 12.68" x 3.05") <sup>viii</sup>
	6.05kg (13.34lbs) <sup>viii</sup>

Getac <sub>3</sub>

Rugged Feature	MIL-STD-810H certified IP66 certified MIL-STD-461G certified <sup>ix</sup> Vibration and 4ft (1.2m) drop resistant Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D) Optional: Salt fog resistant	
Environmental Specification	Temperature <sup>x</sup> : - Operating: -29 C to 63°C / -20°F to 145°F - Storage: -51°C to 71°C / -60°F to 160°F Humidity: - 95% RH, non-condensing	
Pre-installed Software	Getac Utility Getac Geolocation Optional: Absolute Persistence®	
Accessories	Battery (10.8V, typical 6900mAh; min. 6600mAh) x 2 Multimedia bay battery (11.1V, typical 4200mAh; min. 3980mAh) x 1 AC adapter (230W, 100-240VAC, 50/60Hz) <sup>i</sup> Capacitive stylus with tether	
	Optional: Backpack Battery (10.8V, typical 6900mAh; min. 6600mAh) Multimedia bay battery (11.1V, typical 4200mAh; min. 3980mAh) Multi-Bay charger (Dual-Bay) Multimedia bay DVD super multi drive <sup>™</sup> Multimedia bay Blu-Ray super multi drive <sup>™</sup> AC adapter (230W, 100-240VAC, 50/60Hz) <sup>†</sup> MIL-STD-461 AC adapter (230W, 100-240VAC) <sup>†×</sup> DC-DC vehicle adapter (230W, 11-32VDC) Capacitive stylus with tether Protection film Vehicle dock Office dock	

Getac 4

#### **Bumper-to-Bumper Warranty**

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee.

That means you can depend on us to have your unit back in service within days.

### Standard

3 years Bumper-to-Bumper

- I. The configuration with a discrete graphic controller requires the 230W AC adapter.
- II. The 2nd ExpressCard 54 and the 2nd PCMCIA Type II card readers are mutually exclusive.
- III. DVD super multi drive, Blu-Ray super multi drive, and the 2nd multimedia bay battery are mutually exclusive.
- IV. The 3rd Serial port is optional and mutually exclusive with External VGA.
- V. Units with 4G LTE option comes with an embedded SIM card slot.
- VI. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- VII. Dedicated GPS and 4G LTE are mutually exclusive options.
- VIII. Weight and dimensions vary from configurations and optional accessories.
- IX. MIL-STD-461 230W AC adapter sold separately.
- X. Tested by an independent third-party test lab following MIL-STD-810H.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

	Office Dock	Vehicle Dock
Serial Port	1	1
External VGA	1	1
Microphone	1	-
Audio Output	1	-
DC in Jack	1	1
USB	5	6
LAN	2	2
HDMI	1	1
Display port	1	1
RF Antenna Connector	-	1 (GPS, WWAN, WLAN)
Kensington lock	1	1

#### Getac USA

15495 Sand Canyon Ave. Suite 350 Irvine, CA 92618 Tel : 949-681-2900 GetacSales\_US@getac.com I www.getac.com/us/ Copyright © 2022 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

