


















T800 3D demo

T800 FULLY RUGGED TABLET

- 8.1" HD LumiBond[®] display for better viewing experience
- Getac proprietary SnapBack add-on featuring smart card and contactless RFID reader combo or 2nd expanded battery
- Choice of 1D/2D imager barcode reader, Serial port and LAN port (RJ45)
- MIL-STD-810H and IP65 certified
- Enhanced enterprise security with TPM2.0, Windows disk encryption



SPECIFICATIONS

Generation

Operating System
Windows 10 IoT Enterprise

Mobile Computing Platform

Intel® Atom Processor x7-Z8750 1.6GHz, burst up to 2.56GHz

- 2MB Cache

VGA Controller

Intel® HD Graphics

Display 8.1" Wide Viewing Angle TFT LCD WXGA (1280 x 800)

Protection film

600 nits LumiBond® display with Getac sunlight readable technology

Storage & Memory 4GB LPDDR3 Optional: 8GB LPDDR3 128GB eMMC

Optional: 256GB eMMC

Power button

5 tablet programmable buttons

Pointing Device

Touchscreen

- Capacitive multi-touch screen

- Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slots
Optional: 1D/2D imager barcode reader, Serial

port, Ethernet Doptional: SnapBack add-on: Smart card and HF

RFID/NFC reader combo

Optional: SnapBack add-on: 2nd expanded battery "
Optional: SnapBack add-on: Smart card and

magnetic stripe reader

I/O Interface

FHD webcam x 1

8M pixels auto focus rear camera x 1

Audio in/out combo x 1 DC in Jack x 1

USB 3.2 Gen 1 Type-A x 1 Micro HDMI 1.4 x 1

Docking connector x 1

Optional: SIM card slot x 1 (Mini-SIM, 2FF) (Optional: RF antenna pass-through for GPS, WWAN and WLAN

Communication Interface

Intel® Wi-Fi 6 AX200, 802.11ax

Bluetooth (v5.2)

Optional: Dedicated GPS

Optional: 4G LTE mobile broadband " Optional: 10/100/1000 base-T Ethernet

(Occupies expansion slot)

Security Features

TPM 2.0

Optional: SnapBack add-on: Smart card and HF

RFID/NFC combo reader ^{ii, v} Optional: SnapBack add-on: Smart card and

magnetic stripe reader

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

Dimension (W x D x H) & Weight

227 x 151 x 24 mm (8.93" x 5.94" x 0.94") vi 0.88kg (1.94 lbs) '

Rugged Features MIL-STD-810H certified IP65 certified MIL-STD-461G certified Vibration & 6ft (1.8m) drop resistant vii Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D) viii

Environmental Specifications

Temperature

Operating: -21°C to 50°C / -6°F to 122°F Storage: -51°C to 71°C / -60°F to 160°F

Humidity: - 95% RH , non-condensing

Pre-installed software

Getac Utility

Getac Caméra

Getac Barcode Manager * Getac Driving Safety Utility (trial version) Getac KeyWedge Barcode Reader Utility (trial version)

Optional: Absolute Persistence®

Optional software

Getac Driving Safety Utility

Getac KeyWedge Barcode Reader Utility Getac Device Monitoring System (GDMS)

Getac VGPS Utility

Accessories

Battery (7.4V, typical 4200mAh; min. 4080mAh) AC adapter (65W, 100-240VAC) Capacitive stylus with tether

Optional: Carry bag Battery (7.4V, typical 4200mAh; min. 4080mAh)

2nd expanded battery (14.4V, 2100mAh)

Multi-Bay charger (Dual-Bay) Multi-Bay expanded battery dock with adapter (Six-Bay)

Multi-Bay charger (Eight-Bay)
AC adapter (65W, 100-240VAC)
Office dock AC adapter (90W, 100-240VAC)
MIL-STD-461 AC adapter (90W, 100-240VAC)
DC-DC vehicle adapter (120W, 11-32VDC)

Digitizer pen Capacitive stylus with tether Protection film

Hand strap Shoulder strap (2-point) Wrist strap

Vehicle cradle ^{xii} Vehicle dock

Office dock

	Vehicle Dock	Office Dock
Serial Port	1	-
External VGA	-	1
Microphone	1	1
Audio Output	1	1
DC in Jack	1	1
USB	2	4
LAN	1	1
HDMI 1.4	-	1
RF Antenna Connector	3 (WWAN, WLAN, GPS)	-

T800 FULLY **RUGGED TABLET**

Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

- 1D/2D imager barcode reader, Serial port, and Ethernet, are mutually exclusive options.
 All SnapBack add-ons are mutually exclusive
- options.
 Units with 4G LTE option comes with an embedded
- Units with 4G LTE option comes with an embedded SIM card slot. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area. 13.56MHz HF RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant). Weight and dimensions vary from configurations and optional accessories. Drop test results vary from configurations and optional accessories.
- optional accessories.

 Available with limited configurations and
- VIII.
- Available with inflitted configurations and environment conditions.

 Tested by an independent third-party test lab following MIL-STD-810H.

 Available when barcode reader option is selected.

 Models require either embedded or standalone GPS X. XI.
- module.

 XII. Havis vehicle dock is e-mark certified.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.





15495 Sand Canyon Ave. Suite 350 Irvine, CA 92618 Tel : 949-681-2900 GetacSales_US@getac.com I www.getac.com/us/ Copyright © 2022 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only, available specification shall be subjected to quotation by request.