



## S410 RUGGED NOTEBOOK

- Processeur Intel® Core™ i5/i7 vPro™ de 13e génération
- Écran HD / FHD de 14 pouces avec technologie Getac de lecture en plein soleil (1 000 nits) et écran tactile capacitif
- Sécurité d'entreprise améliorée avec la technologie Intel® vPro®, la caméra de reconnaissance faciale Windows Hello, le TPM 2.0 et de nombreuses autres options d'authentification multifacteur
- Connectivité d'E/S polyvalente, notamment Thunderbolt™ 4 et connecteur station d'accueil
- Large plage de températures de fonctionnement comprise entre -29 °C et 63 °C (-20 °F et 145 °F)



En option : Logement de carte SIM (Mini-SIM, 2FF)

Combo entrée/sortie audio

En option : MicroSD

En option: Lecteur de carte à puce

Thunderbolt™ 4 Type-C

Prise d'alimentation CC

HDMI 2.0

USB 3.2 Gen 2 Type-A

LAN

USB 3.2 Gen 1 Type-A

Porte-stylet

En option: 2nd Batterie

En option : Webcam 5MP /  
Caméra de reconnaissance  
faciale Windows Hello

Batterie principale

En option: Économiseur de poids,  
ou lecteur imageur de  
code-barres 1D/2D, ou Lecteur  
DVD Super Multi, ou Lecteur  
Blu-ray Super Mult, ou Batterie  
pour baie multimédia, ou  
Stockage secondaire

Verrou Kensington

Interface E/S en option :

1. Port série + port VGA + 2ème port LAN (RJ45)
2. Port série + port VGA + PowerShare USB 3.2 Gen 1 Type-A
3. Port série + port d'affichage + 2ème port LAN (RJ45)
4. Port série + port d'affichage + PowerShare USB 3.2 Gen 1 Type-A

# SPÉCIFICATIONS

## Generation

G5

## Système d'exploitation

Windows 11 Pro

## Plateforme informatique mobile

Intel® Core™ i5-1340P Processor  
Max. 4.6GHz with Intel® Turbo Boost Technology

- 12 MB Intel® Smart Cache

Platform options:

Intel® Core™ i5-1350P vPro® Processor  
Max. 4.7GHz with Intel® Turbo Boost Technology

- 12 MB Intel® Smart Cache

Intel® Core™ i7-1360P Processor  
Max. 5.0GHz with Intel® Turbo Boost Technology

- 18 MB Intel® Smart Cache

Intel® Core™ i7-1370P vPro® Processor  
Max. 5.2GHz with Intel® Turbo Boost Technology

- 24 MB Intel® Smart Cache

## Contrôleur Graphique

Intel® Iris® Xe Graphics i

Intel® UHD Graphics

Optional: NVIDIA® GeForce® GTX 1650 4GB discrete graphics controller ii, iii, iv

## Écran

14" TFT LCD HD (1366 x 768)

Protection film

1,000 nits display with Getac sunlight readable technology

Optional: 14" TFT LCD HD (1366 x 768)

1000 nits display with Getac sunlight readable technology and capacitive multi-touch screen

Optional: 14" Wide Viewing Angle TFT LCD FHD (1920 x 1080)

1000 nits display with Getac sunlight readable technology

Optional: 14" Wide Viewing Angle TFT LCD FHD (1920 x 1080)

1000 nits display with Getac sunlight readable technology and capacitive multi-touch screen

## Stockage et mémoire

8GB DDR5

Optional: 16GB / 32GB / 64GB DDR5

256GB PCIe NVMe SSD

Optional: 512GB / 1TB / 2TB PCIe NVMe SSD

Optional: Multimedia bay 2nd storage: 512GB / 1TB SATA SSD iii

## Clavier

LED backlit membrane keyboard

## Périphérique de pointage

Touchscreen

- Optional: Capacitive multi-touch screen

Touchpad

- Glide touchpad with multi-touch

## Logement d'extension

Optional: Smart card reader x 1

## Baie multimédia

Weight saver

Optional: 1D/2D imager barcode reader iii

Optional: DVD super multi drive iii, v

Optional: Multimedia bay battery iii, v

Optional: Blu-Ray super multi drive iii, v

Optional: 2nd storage iii, v

## Interface d'E/S

Audio in/out combo x 1

DC in Jack x 1

USB 3.2 Gen 1 Type-A x 1

USB 3.2 Gen 2 Type-A x 2

Thunderbolt™ 4 Type-C x 1

Optional: MicroSD x 1

LAN (RJ45) x 1

HDMI 2.0 x 1

Docking connector x 1

Optional: 5M webcam x 1

Optional: SIM card slot x 1 (Mini-SIM, 2FF) vi

Optional: Windows Hello face-authentication

5M camera (front-facing) x 1 vii

Optional: RF antenna pass-through for GPS, WWAN and WLAN

Configurable I/O options :

1. Serial port (9-pin; D-sub) + VGA port (15-pin; D-sub) + 2nd LAN (RJ45)

2. Serial port (9-pin; D-sub) + VGA port (15-pin; D-sub) + PowerShare USB 3.2 Gen 1 Type-A

3. Serial port (9-pin; D-sub) + Display port + 2nd LAN (RJ45)

4. Serial port (9-pin; D-sub) + Display port + PowerShare USB 3.2 Gen 1 Type-A

## Interface de communication

10/100/1000 base-T Ethernet

Intel® Wi-Fi 6E AX211, 802.11ax

Bluetooth (v5.3) viii

Optional: Dedicated L1/L5 GPS ix

Optional: 4G LTE mobile broadband with integrated GPS vi, x, xi

Optional: 5G Sub-6 with integrated L1/L5 GPS

vi, ix, x, xi

Dual SIM (Mini-SIM 2FF and e-SIM) xii

## Fonctionnalités de sécurité

TPM 2.0

Kensington lock

Optional: Intel® vPro® Technology

Optional: Fingerprint reader

Optional: HF RFID reader xiii

Optional: Smart card reader

Optional: Windows Hello face-authentication

5M camera (front-facing) vii

## Alimentation

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (10.8V, typical 6900mAh; min. 6600mAh)

Optional: AC adapter (120W, 100-240VAC, 50/60Hz) ii

Optional: Multimedia bay battery (11.1V, typical 4200mAh; min. 3980mAh) iii

Optional: 2nd battery (10.8V, typical 6900mAh; min. 6600mAh)

## Dimensions (l x P x H) et poids

350 x 293 x 38.5mm (13.8" x 11.5" x 1.5")

2.38kg (5.25lbs) xiv

## Caractéristiques de conception renforcée

MIL-STD-810H certified

IP53 certified

Splash resistant keyboard

Vibration & 3ft (0.9m) drop resistant xv

Sealed ports and connectors

Shock-protected removable SSD

## Spécifications environnementales

Temperature xvi :

- Operating: -29°C to 63°C / -20°F to 145°F xvii

- Storage: -51°C to 71°C / -60°F to 160°F

Humidity:

- 95% RH, non-condensing

## Logiciels préinstallés

Getac Utility

Getac Geolocation

Getac Barcode Manager xviii

Optional: Absolute Persistence®

## Logiciel en option

Getac Driving Safety Utility

Getac Device Monitoring System (GDMS)

Getac VGPS Utility xix

# S410 RUGGED NOTEBOOK

## Accessoires

Battery (10.8V, typical 6900mAh; min. 6600mAh)

AC adapter (90W, 100-240VAC, 50/60Hz)

Capacitive stylus with tether

Optional:

Carry bag

Battery (10.8V, typical 6900mAh; min. 6600mAh)

Multimedia 2nd SSD iii

Multimedia bay battery (11.1V, typical 4200mAh; min. 3980mAh) iii

Multi-Bay charger (Dual-Bay)

Multi-Bay charger (Eight-Bay)

AC adapter (120W, 100-240VAC, 50/60Hz) ii

DC-DC vehicle adapter (120W, 11-32VDC)

Capacitive stylus with tether

Protection film

Vehicle cradle xx

Vehicle dock xx

Office dock

100W Type-C adapter xxi

## Garantie

Rien n'est plus synonyme de qualité qu'un fabricant fier de son produit. Nous avons conçu l'ordinateur portable de l'intérieur pour résister aux chutes, aux chocs, aux déversements, aux vibrations et plus encore. Nous avons confiance en notre qualité et c'est pourquoi il est livré en standard avec une garantie de 3 ans, la meilleure du secteur. C'est la tranquillité d'esprit de savoir que vous êtes couvert.

## Standard

Garantie limitée de 3 ans

i. Units equipped with dual channel memory come with Intel® Iris® Xe Graphics. ii. 120W AC adapter is used for office dock and for device configured with discrete graphics card. iii. NVIDIA® GeForce® GTX 1650 4GB discrete graphics controller, Blu-Ray, DVD super multi drive, Multimedia bay battery, 1D/2D imager barcode reader and 2nd storage are mutually exclusive options. iv. NVIDIA® GeForce® GTX 1650 4GB discrete graphics controller is required to configure with Intel® Core™ i5/i7 processor, Dual battery, FHD LCD display with capacitive multi-touch screen, and 120W AC adapter. v. Trained user swappable. vi. Units with 4G/5G option come with an embedded SIM card slot. vii. 5M webcam and optional Windows Hello face-authentication camera (front-facing) are mutually exclusive options. viii. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area. ix. Support GPS, GLONASS, Galileo, BeiDou and QZSS. x. Only available in the US, UK, EU, Australia, and New Zealand. xi. Support GPS, GLONASS, Galileo and BeiDou. xii. One physical SIM card slot and one eSIM. Network service may vary depending on local telecommunication providers. xiii. 13.56MHz HF RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant). xiv. Weight and dimensions vary from configurations and optional accessories. xv. Drop test results vary from configurations and optional accessories. xvi. Tested by an independent third-party test lab following MIL-STD-810H. xvii. For S410 optional DVD / Blu-Ray super-multi drive, the operating temperature is -10°C to 50°C / 14°F to 122°F. xviii. Available when barcode reader option is selected. xix. Models require either embedded or standalone GPS module. xx. Havis vehicle dock is e-mark certified. xxi. Do not support the configurations with discrete graphics card.

# Getac

GETAC TECHNOLOGY CORPORATION

12, avenue du Québec Bâtiment Goyave  
91140 Villebon sur Yvette Tel: +33 160 12  
80 60 Sales-Getac-France@getac.com |

www.getac.com/fr/

Copyright © 2023 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Les informations sont fournies ici pour référence seulement, les spécifications disponibles doivent faire l'objet d'un devis sur demande.

	Station d'accueil pour véhicule	Station d'accueil pour bureau
Port série	1	1
Port VGA externe	1	1
Micro	1	1
Sortie audio	1	1
Prise d'alimentation CC	1	1
Port USB	4	USB 3.0 x 1 USB 2.0 x 3

	Station d'accueil pour véhicule	Station d'accueil pour bureau
Port LAN	1	1
Port HDMI	1	1
Connecteur d'antenne RF	3 (WWAN, WLAN et GPS)	-