




T800-EX FULLY RUGGED TABLET

- 8.1" HD LumiBond display for better viewing experience
- MIL-STD-810H and IP65 certified
- Enhanced enterprise security with TPM2.0, Windows disk encryption



T800-EX 3D
demo



SPECIFICATIONS

Generation

G2

Operating System

Windows 10 IoT Enterprise

Mobile Computing Platform

Intel® Atom Processor x7-Z8750 1.6GHz,
burst up to 2.56GHz
- 2MB Cache

VGA Controller

Intel® HD Graphics

Display

8.1" Wide Viewing Angle TFT LCD WXGA (1280 x 800)

Protection film

600 nits LumiBond display with Getac sunlight readable technology

Storage & Memory

4GB LPDDR3

Optional: 8GB LPDDR3

128GB eMMC

Optional: 256GB eMMC

Keyboard

Power button

5 tablet programmable buttons

Pointing Device

Touchscreen

- Capacitive multi-touch screen

- Optional dual mode touchscreen (multi-touch and digitizer)

Expansion Slots

Optional: SnapBack add-on: 2nd expanded battery

Optional: 1D/2D imager barcode reader x 1

I/O Interface

FHD webcam x 1

8M pixels auto focus rear camera x 1

Audio in/out combo x 1

DC in Jack x 1

USB 3.2 Gen 1 Type-A x 1

Micro HDMI 1.4 x 1

Optional: SIM card slot x 1 (Mini-SIM, 2FF) ⁱ

Communication Interface

Intel® Wi-Fi 6 AX200, 802.11ax

Bluetooth (v5.2) ⁱⁱ

Optional: Dedicated GPS

Optional: 4G LTE mobile broadband ⁱ

Security Features

TPM 2.0

Power

AC adapter (65W, 100-240VAC, 50/60Hz)

Li-ion battery (7.4V, typical 4200mAh; min. 4080mAh)

Dimension (W x D x H) & Weight

227 x 151 x 24 mm (8.93" x 5.94" x 0.94") ⁱⁱⁱ

0.91kg (2lbs) ⁱⁱⁱ

Rugged Features

MIL-STD-810G certified

IP65 certified

Vibration & 6ft (1.8m) drop resistant ^{iv}

ATEX & IECEx certified

Environmental Specifications

Temperature ^v:

- Operating: -21°C to 50°C / -6°F to 122°F

- Storage: -51°C to 71°C / -60°F to 160°F

Humidity:

- 95% RH, non-condensing

Explosion Protection

ATEX/IECEx Zone 2/22

Ex II 3G Ex ic op is IIC T4 Gc

Ex II 3D Ex ic op is IIIB T130°C Dc

Pre-installed software

Getac Utility

Getac Camera

Getac Barcode Manager ^{vi}

Getac Driving Safety Utility (trial version)

Getac KeyWedge Barcode Reader Utility (trial version)

Optional: Absolute Persistence®

Optional software

Getac Driving Safety Utility

Getac KeyWedge Barcode Reader Utility

Getac Device Monitoring System (GDMS)

Getac VGPS Utility ^{vii}

Accessories

Battery (7.4V, typical 4200mAh; min. 4080mAh)

AC adapter (65W, 100-240VAC)

Capacitive stylus with tether

Optional:

Battery (7.4V, typical 4200mAh; min. 4080mAh)

2nd expanded battery (14.4V, 2100mAh)

AC adapter (65W, 100-240VAC)

Digitizer pen

Capacitive stylus with tether

Protection film

Shoulder strap (2-point)

Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

T800-EX FULLY RUGGED TABLET

- I. Units with 4G LTE option come with an embedded SIM card slot.
- II. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- III. Weight and dimensions vary from configurations and optional accessories.
- IV. Drop test results vary from configurations and optional accessories.
- V. Tested by an independent third-party test lab following MIL-STD-810H.
- VI. Available when barcode reader option is selected.
- VII. Models require either embedded or standalone GPS module.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

Getac



Getac (UK) Ltd.

Getac House, Stafford Park 12, Telford,
Shropshire TF3 3BJ, United Kingdom Tel :
+44 (0) 1952 207 222 Sales-Getac-
UK@getac.com | www.getac.com/en/
Copyright © 2022 Getac Technology Corporation
and/or any of its affiliates. All Rights Reserved.
Information provided herewith is for reference
only, available specification shall be subjected to
quotation by request.