# Getac



# ZX70-EX FULLY RUGGED TABLET

- Compatible with Android Enterprise
- 7" LumiBond® Display with Getac Sunlight Readable Technology and Glove-enabled Capacitive Touchscreen
- ATEX & IECEx Explosive Atmosphere Certified
- 6 Feet Drop , MIL-STD-810H and IP67 Certified
- Optional Barcode Reader and HF RFID
- Optional 4G LTE WWAN















## **Specifications**

#### Generation

#### **Operating System**

Android 9.0

#### **Mobile Computing Platform**

Qualcomm® Snapdragon™ 660, Octa-core 1.95 GHz, burst up to 2.2 GHz

#### **VGA Controller**

Qualcomm® Adreno™ 512 GPU

7" IPS TFT LCD HD (1280 x 720) LumiBond® display with Getac sunlight readable technology Capacitive touchscreen with glove on

#### Storage & Memory

4GB LPDDR4 64GB storage

### **Keyboard**

4 tablet buttons ( Power, Barcode Launch Button, Volume Up, Volume Down)

#### **Pointing Device**

Touchscreen

- Capacitive multi-touch screen

#### **Expansion Slot**

MicroSD x1

#### I/O Interface

8M pixels webcam x 1 12M pixels auto focus rear camera x 1 MicroUSB 2.0 (Client) x 1 USB 2.0 (Host) x 1 DC in Jack x 1

#### **Communication Interface**

Wi-Fi 802.11ac Bluetooth (v5.0)i Dedicated GPS
Optional 4G LTE mobile broadband

#### **Security Feature**

Optional Contactless HF RFID/NFC combo reader<sup>ii,iii</sup> Optional Barcode reader

AC adapter (25W, 100-240VAC, 50 / 60Hz) Li-lon battery (3.8V, typical 8480mAh; min. 8220mAh)

#### Dimension (W x D x H) & Weight

218 x 142 x 27 mm (8.58 " x 5.6" x 1.08") 762g (1.68lbs)iv

## **Rugged Feature**

MIL-STD-810H certified and IP67 certified 6 feet drop resistant<sup>v</sup> ATEX & IECEx Explosive Atmosphere Certified

#### **Environmental Specification**

#### Temperature<sup>v</sup>:

- Operating: -21°C to 60°C / -6°F to 140°F Storage: -40°C to 71°C / -40°F to 160°F
- 95% ŔH , non-condensing

ATEX / IECEx Zone 2/22 II 3G Ex ic op is IIC T5 Gc II 3D Ex ic op is IIIB T100°C Dc

Getac Settings and Google Applications (Search, Chrome, Gmail, Maps, YouTube, Play, Drive, Play Music, Play Movies, Duo and Photos)

#### **Accessories**

AC adapter (25W; 12V/2A, 100-240VAC; 50 / 60 Hz) Capacitive stylus Hand strap with Stylus Holder Wrist strap

Anti-static protection film

#### **Bumper-to-Bumper warranty**

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment

That is why Getac has introduced accidental damage as standard under our new Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

#### Standard

3 years Bumper-to-Bumper.

- Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is
- operating in the area. 13.56MHz Contactless HF RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™
- compliant).

  iii HF RFID/NFC combo reader applies to US & EU
  iv Weight and dimensions vary from
- configurations and optional accessories.
  Tested by a national independent third party test lab following MIL-STD-810H.

## ZX70-Ex **Fully Rugged Tablet**





#### Getac (UK) Ltd.

Getac House, Stafford Park 12, Telford, Shropshire TF3 3BJ, United Kingdom Tel: +44 (0) 1952 207 222 Sales-Getac-UK@getac.com | www.getac.com/en/



Copyright @ 2020 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved ation provided herewith is for reference only available specification shall be subjected to quotation by request. V01M07Y20UK