

B360 Pro ACCESSORY SPEC BROCHURE



Getac (UK) Ltd.

Getac House, Stafford Park 12, Telford, Shropshire TF3 3BJ, United Kingdom
Tel : +44 (0) 1952 207 222 Sales-Getac-UK@getac.com | www.getac.com/en/

CARRY BAG

Features & Benefits

Constructed of durable Nylon/air mesh fabric and featuring an adjustable padded shoulder strap, this compact carry bag provides sturdy protection for your device while giving maximum comfort. The functional pockets inside offer the optimal solution to transport the laptop and needed accessories together in one case, delivering extra convenience and go-anywhere productivity to mobile professionals.

Product Information

Dimensions : L 405 x W 330 x D 100mm
Weight : 1.335kg
Main Material : Nylon, air mesh fabric

SKU ID

GMBCX7



B360 EXTERNAL DUAL BAY BATTERY CHARGER

Features & Benefits

Getac B360 External Dual-Bay Charger is designed to charge up to 2 B360 batteries at the same time. It provides you the benefit of charging and storing the 2 batteries together when there are limited space and power sockets. The two bays have two channels, each with their own LED power indicators. The integrated five-light LED power indicators display the charge of each battery.

Product Information

AC Input : 100V~240V
 DC Output : 17.4V, 4A Max.
 Number of charge bays : 2 bays
 Dimensions : L 160 x W 180 x H 72.5mm
 Weight : 1.2kg
 Compatible with both B360 (GBM3X6) and B360Pro (GBM6X5) system battery.

SKU ID

| | |
|---|---|
| Two Main Batteries | Main + Multimedia Bay Battery |
| GCMCEH (EU Power Cord) GCMCUH (US Power Cord) GCMCKH (UK Power Cord) GCMCAH (AU Power Cord) GCMCCH (CHN Power Cord) GCMCTH (TW Power Cord) | GCMCEN (EU Power Cord) GCMCUN (US Power Cord) GCMCKN (UK Power Cord) GCMCAN (AU Power Cord) GCMCCN (CHN Power Cord) GCMCTN (TW Power Cord) |



B360 MULTI BAY BATTERY CHARGER

Features & Benefits

This 8-bay battery charger is designed with 8 charging bays for charging multiple battery packs simultaneously, providing an efficient charging solution for different situations. It provides users with an efficient charging solution. The integrated five-light LED power indicators display the charge of each battery.

Product Information

AC Input : 100V~240V AC, 4.2A 50~60Hz

DC Output : 19.5V, 16.9A

* w / 330W AC Adapter

Number of charge bays: 8 bays

Dimensions : L 465 x W 245 x H 101~117.4 mm

Weight : 4.7 kg, not including battery packs

Compatible with both B360 (GBM3X6) and B360Pro (GBM6X5) system battery.

SKU ID

GCECEL (EU Power Cord)

GCECUL (US Power Cord)

GCECKL (UK Power Cord)

GCECAL (AU Power Cord)

GCECCL (CHN Power Cord)

GCECTL (TW Power Cord)



B360 PRO SPARE MAIN BATTERY

Features & Benefits

Getac B360 Pro Spare Main Battery is designed to provide the main power source for your device when the AC adapter is not connected. Designed with an integrated LED power indicator and status check button, allow the user to identify the battery capacity status at the push of a button.

Product Information

Battery type : Lithium-ion
Cell designation : 3S2P
Output Voltage : 10.8V
Capacity : typical 6900mAh; min. 6600mAh
Dimensions : L 141.05 x W 73.8 x H 22.3mm
Weight : 345.6g

SKU ID

GBM6X5



100W TYPE-C AC ADAPTER

Features & Benefits

The 100W Type-C AC adapter as an additional charging solution to charge Getac rugged tablets and laptops with inherent USB type-C ports as well as the power delivery functionality. The Type-C adapter features a reversible connector type that reduces connector damages due to misuse.

Product Information

Input : 100V-240V
Output : 20V, 5A, 100W
Dimensions : L 140 x W 65 x H 25mm
Weight : 326g
Input cable length : 1830mm
Output cable length : 1500mm

SKU ID

GAT1E1 (EU Power Cord)
GAT1U1 (US Power Cord)
GAT1K1 (UK Power Cord)
GAT1A1 (AU Power Cord)
GAT1C1 (CHN Power Cord)
GAT1T1 (TW Power Cord)
GAT1I1 (IN Power Cord)



120W AC ADAPTER WITH POWER CORD

Features & Benefits

Specifically designed for use with the office docking station and performance SKU, this 120W AC adapter provides efficient delivery to power your devices.

Product Information

Input : 100V-240V
Output : 19V, 6.32A Max.
Dimensions : L 131.5 x W 69 x H 25.6mm
Weight : 412g
Input cable length : 1830mm
Output cable length : 1800mm

SKU ID

GAA3E2 (EU Power Cord)
GAA3U2 (US Power Cord)
GAA3K2 (UK Power Cord)
GAA3A2 (AU Power Cord)
GAA3C2 (CHN Power Cord)
GAA3T2 (TW Power Cord)
GAA3R2 (KR Power Cord)
GAA3I2 (IN Power Cord)
GAA3G2 (AG Power Cord)



90W AC ADAPTER

Features & Benefits

This adapter is designed to power the device and charge its internal battery from an AC power source. A country-specific power cord is included with the adapter to fit the local power outlet in your destination country.

Product Information

Input : 100V-240V

Output : 19V, 4.74 A, 90W

Dimensions : L 140.1 x W 65.1 x H 25.4 mm

Weight : 275 g

Input cable length : 1830mm

Output cable length: 1500mm

SKU ID

GAA9U7 (US Power Cord)

GAA9E7 (EU Power Cord)

GAA9K7 (UK Power Cord)

GAA9C7 (CHN Power Cord)

GAA9A7 (AU Power Cord)

GAA9T7 (TW Power Cord)

GAA9I7 (IN Power Cord)

GAA9G7 (ARG Power Cord)

GAA9J7 (JPN Power Cord)

GAA9R7 (KR Power Cord)



90W MIL-STD-461 AC ADAPTER

Features & Benefits

This MIL-STD-461G AC adapter has passed the military standard and testing specification to ensure the conducted emissions (CE), conducted susceptibility (CS), radiated emissions (RE), and radiated susceptibility (RS) of the adapter can meet the requirements for the control of electromagnetic interference.

Product Information

Input : 115V-230V, 1.6A 50~60Hz
Output : 19V, 4.74A, 90W
Dimensions : L 170 x W 75 x H 45mm
Weight : 880g (without power cord)
Input cable length : 1530mm
Output cable length : 1800mm

SKU ID

GAAGE5 (EU Power Cord)
GAAGU5 (US Power Cord)
GAAGK5 (UK Power Cord)
GAAGC5 (CHN Power Cord)
GAAGA5 (AU Power Cord)
GAAGI5 (IN Power Cord)
GAAGT5 (TW Power Cord)



B360 OFFICE DOCK WITH AC ADAPTER

Features & Benefits

The Getac office dock brings out multiple I/O ports for connecting essential peripheral devices in the office environment. Through the integrated ethernet, RS232, or USB connections, users can quickly collect and synchronize field data with central offices for real-time reporting and analytics.

Product Information

Dimensions : L 380.1 x W 291.2 x H 77.2 mm

Weight : 1.615kg * w / 120W AC Adapter

I/O Ports : DC in Jack x 1, Audio Output x 1, Microphone x 1, USB 2.0 x 2,
USB 3.0 x 3, LAN x 2, HDMI x 1, VGA x 1, Serial Port x 1, Kensington Lock x 1

SKU ID

GDODE1 (EU Power Cord)

GDODU1 (US Power Cord)

GDODK1 (UK Power Cord)

GDODA1 (AU Power Cord)

GDODC1 (CHN Power Cord)

GDODT1 (TW Power Cord)



CAPACITIVE HARD TIP STYLUS & TETHER

Features & Benefits

This capacitive stylus is lightweight and easy to control, allowing smooth and comfortable interaction with the touch screen without worrying about scratching the screen or leaving fingerprints on it. The stylus comes with a tether to keep it attached to the tablet, so it doesn't get lost or misplaced.

Product Information

Stylus Dimensions : 108.7 mm ; Ø9 mm
Tip size : 2.7 mm ; Ø2.8 mm
Color : Black
Tether Length : 304 mm

SKU ID

GMPSXK



GETAC DS100 USB-C DOCKING STATION

Features & Benefits

The Getac DS100 USB-C Docking Station, featuring a slim and compact design, seamlessly consolidates cables on the workstation. This allows users to swiftly create a personalized workspace and organize their daily office environment. Compatible with various Getac laptop and tablet models, it provides extra connectivity and multiple I/O ports for additional peripherals and data sources. With support for MAC Address Pass-Through, Wake-on-LAN (WoL), and PXE Boot, the DS100 aids IT administrators in maintaining a secure, efficient, and well-managed network infrastructure. (The docking station's performance, including transfer speeds and display capabilities, may be limited by chipset and operating system when used with Getac Android systems. See the user manual for details.)

Product Information

Dimensions: L 207 x W 90 x H 31mm (8.15" x 3.54" x 1.22")

Weight: 335g (0.74lbs)

Power Cable Length: 1.8m (5.9ft)

USB-C Upstream Cable Length: 1m (3.28ft)

I/O Ports: DC in Jack x 1, Audio in/out combo x 1, USB 2.0 x 2, USB 3.2

Gen 1 Type-A x 2, USB 3.2 Gen 2 Type-C x 2, LAN x 1, HDMI 2.0 x 1,

Display port x 2

SKU ID

GDDSE1 (EU Power Cord)

GDDSU1 (US Power Cord)


GDDSK1 (UK Power Cord)

GDDSA1 (AU Power Cord)

GDDSC1 (CHN Power Cord)

GDDST1 (TW Power Cord)

GDDSI1 (IN Power Cord)



B360 PROTECTION FILM AG

Features & Benefits

This screen protection film is cut precisely to fit the B360 Fully Rugged Notebook and is easy to install and remove without leaving a sticky residue. With anti-glare coating, it not only protects the screen from the rigors of daily use but also help diffuses light on the screen and reduces glare, providing effortless readability for displayed information under common ambient lighting conditions.

Product Information

Dimensions : L 303.0 x W 174.6 x 0.24mm
Main Material : PET

SKU ID

GMPFXP



B360 MAIN STORAGE WITH CANISTER

Features & Benefits


Getac B360 Main Storage with canister is designed to provide you the ease of installation and allow you to remove your confidential data when your device is sent for service.

Product Information

SSD Storage option : 256GB, 512GB, 1TB, 2TB
Type : PCIe NVMe SSD
Dimensions : L 110.5 x W 27 x H 5mm

SKU ID

GSSEX3 (256GB PCIe SSD)
GSSFX3 (512GB PCIe SSD)
GSSGX3 (1TB PCIe SSD)
GSSHX1 (2TB PCIe SSD)



120W DC-DC VEHICLE ADAPTER

Features & Benefits

The 120W vehicle adapter comes with a choice of two types of connections: a bare wire with individual wire ends already stripped, and a cigarette lighter plug for easy connection to the cigarette lighter socket in the vehicle interior, providing a convenient way to charge and power your tablet while you are on the road.

Product Information

Input Voltage : 11VDC~ 32VDC

Output Voltage : 19VDC

Output current : 6.32A Max.

Case Dimensions : L 131.5 x W 65.6 x H 30mm

Weight : 362g

Input cable length : 1900mm

Output cable length : 1000mm

SKU ID

GAD2X4 (Cigarette Lighter Plug Version)

GAD2X8 (Bare Wire Version)

