


## X600 PRO FULLY RUGGED LAPTOP



- 11th Generation Intel® Core™ i7 / i5 vPro® Processor
- 15.6" FHD LumiBond display with Getac sunlight readable technology (1,000 nits) and optional capacitive touchscreen
- Enhanced enterprise security features with TPM 2.0, Kensington lock, triple user-replaceable storage and Smart card reader
- Versatile I/Os connectivity including Thunderbolt™ 4 and docking solutions
- Optional discrete graphic NVIDIA® Quadro® RTX3000
- Expandable modules for additional ports, batteries, DVD super multi drive, and connectivity



X600 Pro 3D demo



## SPECIFICATIONS

### Generation

G1

### Operating System

Windows 11 Pro

### Mobile Computing Platform

Intel® Core™ i5-11500HE vPro® Processor  
Max. 4.5GHz with Intel® Turbo Boost Technology  
- 12MB Intel® Smart Cache

### Platform options:

Intel® Core™ i7-11850HE vPro® Processor  
Max. 4.7GHz with Intel® Turbo Boost Technology  
- 24MB Intel® Smart Cache

Intel® Xeon® W-11865MRE vPro® Processor  
Max. 4.7GHz with Intel® Turbo Boost Technology  
- 24 MB Intel® Smart Cache

### VGA Controller

Intel® UHD Graphics  
Optional: NVIDIA® Quadro®  
RTX3000 6GB discrete graphics controller<sup>i,ii,iii</sup>  
Optional: NVIDIA® GeForce®  
GTX1650 4GB discrete graphics controller<sup>i,ii</sup>

### Display

15.6" TFT LCD FHD (1920 x 1080)  
Protection film  
1,000 nits LumiBond display  
with Getac sunlight readable technology  
Optional: Capacitive multi-touch screen

### Storage & Memory

16GB DDR4  
Optional: 32GB / 64GB / 128GB DDR4

512GB PCIe SSD  
Optional: 1TB / 2TB PCIe SSD  
Optional 2<sup>nd</sup> storage: 512GB / 1TB / 2TB PCIe SSD  
Optional 3<sup>rd</sup> storage: 512GB / 1TB / 2TB PCIe SSD

### Keyboard

LED backlit membrane keyboard  
with integrated numeric keypad

### Pointing Device

Touchscreen  
- Optional: Capacitive multi-touch screen  
Touchpad  
- Touchpad with two buttons

### Expansion Slot

Smart card reader  
ExpressCard 54 + PCMCIA Type II  
Optional: 2<sup>nd</sup> ExpressCard 54 or 2<sup>nd</sup>  
PCMCIA Type II<sup>iv</sup>  
Optional: SD card reader

### Multimedia Bay

Multimedia bay battery (11.1V, typical 4200mAh;  
min. 3980mAh)  
DVD super multi drive<sup>v</sup>  
Optional: Multimedia bay 2<sup>nd</sup> battery  
(11.1V, typical 4200mAh; min. 3980mAh)  
or Blu-Ray super multi drive<sup>v</sup>

### I/O Interface

5M webcam x 1  
Thunderbolt™ 4 Type-C x 1  
USB 3.2 Gen 2 Type-A x 4  
LAN (RJ-45) x 2  
Audio in/out combo x 1  
DC in Jack x 1  
HDMI 2.0 x 1  
Display port x 1  
Docking connector x 1  
Serial port (9-pin; D-sub) x 2  
External VGA (15-pin; D-sub) x1 or 3<sup>rd</sup> serial  
port (9-pin; D-sub) x 1<sup>vi</sup>  
Optional: SIM card slot x 1 (Mini-SIM, 2FF)<sup>vii</sup>  
Optional: RF antenna pass-through for GPS,  
WWAN and WLAN x 1

### Communication Interface

2.5GBASE-T Ethernet  
Intel® Wi-Fi 6E AX210, 802.11ax  
Bluetooth (v5.2)<sup>viii</sup>  
Optional: Dedicated GPS<sup>ix</sup>  
Optional: 4G LTE mobile broadband  
with integrated GPS<sup>xii,ix</sup>

### Security Feature

TPM 2.0  
Kensington lock  
Smart card reader  
Intel® vPro® Technology

### Power

AC adapter (230W, 100-240VAC, 50/60Hz)<sup>i</sup>  
Battery (10.8V, typical 6900mAh;  
min. 6600mAh) x 2  
Multimedia bay battery (11.1V, typical 4200mAh;  
min. 3980mAh) x 1  
Optional: Multimedia bay 2<sup>nd</sup> battery  
(11.1V, typical 4200mAh; min. 3980mAh)<sup>v</sup>

### Dimension (W x D x H) & Weigh

412 x 322 x 77.4mm (16.22" x 12.68" x 3.05")<sup>x</sup>  
6.05kg (13.34lbs)<sup>x</sup>

### Rugged Feature

MIL-STD-810H certified  
IP66 certified  
MIL-STD-461G certified<sup>xi</sup>  
Vibration and 4ft (1.2m) drop resistant  
Optional: ANSI/UL 121201, CSA C22.2 NO. 213  
(Class I, Division 2, Groups A, B, C, D)  
Optional: Salt fog certified

### Environmental Specification

Temperature<sup>xii</sup>:  
- Operating: -29°C to 63°C / -20°F to 145°F  
- Storage: -51°C to 71°C / -60°F to 160°F  
Humidity:  
- 95% RH, non-condensing

### Pre-installed Software

Getac Utility  
Getac Geolocation  
Optional: Absolute Persistence®

### Accessories

Battery (10.8V, typical 6900mAh; min. 6600mAh) x 2  
Multimedia bay battery (11.1V, typical 4200mAh;  
min. 3980mAh) x 1  
AC adapter (230W, 100-240VAC, 50/60Hz)<sup>i</sup>  
Capacitive stylus with tether

### Optional:

Backpack  
Battery (10.8V, typical 6900mAh; min. 6600mAh)  
Multimedia bay battery (11.1V, typical 4200mAh;  
min. 3980mAh)  
Multi-Bay charger (Dual-Bay)  
Multimedia bay DVD super multi drive<sup>v</sup>  
Multimedia bay Blu-Ray super multi drive<sup>v</sup>  
AC adapter (230W, 100-240VAC, 50/60Hz)<sup>i</sup>  
Office dock AC adapter (230W, 100-240VAC,  
50/60Hz)<sup>i</sup>  
MIL-STD-461 AC adapter (230W, 100-240VAC)<sup>xi</sup>  
DC-DC vehicle adapter (230W, 11-32VDC)  
Capacitive stylus with tether  
Protection film  
Vehicle dock  
Office dock  
DS100 USB-C docking station  
Spare SSD kit

### Bumper-to-Bumper warranty

Gli imprevisti possono compromettere l'utilizzo dei dispositivi e causare costosi tempi di inattività. Ecco perché Getac ha introdotto la copertura dei danni accidentali come standard della garanzia Bumper-to-Bumper, consentendo una migliore gestione dei costi legati all'IT. Bumper-to-Bumper è la garanzia senza problemi. Questo significa che potete contare su di noi affinché il vostro dispositivo sia nuovamente operativo nel giro di pochi giorni.

### Standard

3 anni Bumper-to-Bumper

# X600 PRO FULLY RUGGED LAPTOP

- I. The configuration with a discrete graphic controller requires the 230W AC adapter.
- II. 150W AC adaptor is not applicable with discrete graphic controller nor office dock.
- III. For X600 Pro optional NVIDIA® Quadro® RTX3000, the operating temperature is 0°C to 63°C / 32°F to 145°F.
- IV. The 2<sup>nd</sup> ExpressCard 54 and the 2<sup>nd</sup> PCMCIA Type II card readers are mutually exclusive.
- V. DVD super multi drive, Blu-Ray super multi drive, and the 2<sup>nd</sup> multimedia bay battery are mutually exclusive.
- VI. The 3<sup>rd</sup> Serial port is optional and mutually exclusive with External VGA.
- VII. Units with 4G LTE option comes with an embedded SIM card slot.
- VIII. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- IX. Dedicated GPS and 4G LTE are mutually exclusive options.
- X. Weight and dimensions vary from configurations and optional accessories.
- XI. MIL-STD-461 230W AC adapter sold separately.
- XII. Tested by an independent third-party test lab following MIL-STD-810H.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

	Office Dock	Vehicle Dock
Serial Port	1	1
External VGA	1	1
Microphone	1	-
Audio Output	1	-
DC in Jack	1	1
USB	5	6
LAN	2	2
HDMI	1	1
Display port	1	1
RF Antenna Connector	-	1 (GPS, WWAN, WLAN)
Kensintonlock	1	1

# Getac



GETAC TECHNOLOGY CORPORATION

Via Paracelso 26, Centro Direzionale Colleoni,  
Palazzo Cassiopea 3 20864 Agrate Brianza (MB)  
Tel: +39 039 8901584

Sales-getac-Italy@getac.com | www.getac.com/it/

Copyright © 2023 Getac Technology Corporation  
and/or any of its affiliates. All Rights Reserved.  
Information provided herewith is for reference  
only, available specification shall be subjected to  
quotation by request.